


1 LOCATION OF WATER WELL:	FRACTION				Section Number	Township Number	Range Number				
Butler	SW	1/4	NE	1/4	NW	1/4	31	T 27 S	R 3E EW		
Distance and direction from nearest town or city street address of well if located within city?											
3/8 m. E. of 159th Nd 1/4 S. of Harry					Andover, Kansas						
2 WATER WELL OWNER:	ARBUCKLE, Larry				Board of Agriculture, Division of Water Resource						
RR#, ST. ADDRESS, BOX #:	1119 N. Harry				Application Number:						
CITY, STATE, ZIP CODE:	Andover, Kansas										
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL	56	ft.	ELEVATION:			
Depth(s) groundwater Encountered					1	ft.	2	ft.	3	ft.	
WELL'S STATIC WATER LEVEL 10					FT. BELOW LAND SURFACE MEASURED ON mo/day/yr					07/12/1995	
Pump test data: Well water was					ft.	after	hours pumping	gpm			
Est. Yield	gpm:	Well water was	ft.	after	hours pumping	gpm					
Bore Hole Diameter	12	in. to 56	ft.	and	in. to	ft.					
WELL WATER TO BE USED AS:					5 Public water supply	8 Air conditioning	11 Injection well				
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)							
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes					No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was						
submitted					Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>						
5 TYPE OF CASING USED:					CASING JOINTS:						
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	Glued <input checked="" type="checkbox"/> Clamped							
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (Specify below)	Welded							
Blank casing Diameter 6 in. to 25 ft., Dia				SDR-26				Threaded			
Casing height above land surface 12 in., weight 3.25 lbs. / ft.				7 PVC				.255			
TYPE OF SCREEN OR PERFORATION MATERIAL:				10 Asbestos-cement							
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 other (specify)							
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)							
SCREEN OR PERFORATION OPENING ARE:					8 Saw cut					11 None (open hole)	
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	9 Drilled holes								
2 Louvered shutter	4 Key punched	6 Wire wrapped	10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 25 ft. to 56 ft., From					ft. to					ft.	
from					ft. to					ft.	
GRAVEL PACK INTERVALS: from 24 ft. to 56 ft., From					ft. to					ft.	
from					ft. to					ft.	
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other							
Grout Intervals: From 4 ft. to 24 ft. From					ft. From					ft. to	
What is the nearest source of possible contamination:										ft.	
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens						14 Abandon water well		
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage						15 Oil well/Gas well		
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage						16 Other (specify below)		
None Apparent										ft.	
Direction from well?										How many feet?	
FROM	TO	LITHOLOGIC LOG				FROM	TO	PLUGGING INTERVALS			
0	3	topsoil									
3	21	clay									
21	56	gray shale									
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/12/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 07/13/95.										
Under the business name of Harp Well & Pump Service, Inc. by (signature)										Jane Frederick	