

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: <u>Bottler</u>		<u>SE 1/4 NW 1/4 NW 1/4</u>		<u>25</u>		T <u>27</u> S		R <u>3</u> <u>EW</u>			
Distance and direction from nearest town or city street address of well if located within city? <u>4 W Augusta</u>											
2 WATER WELL OWNER: <u>Joe B Aranda</u>					Board of Agriculture, Division of Water Resources						
RR#, St. Address, Box #: <u>130 S. Greenwich Rd</u>					Application Number:						
City, State, ZIP Code: <u>Wichita, KS 67216</u>											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL <u>90</u> ft. ELEVATION:								
			Depth(s) Groundwater Encountered 1. <u>65</u> ft. 2. ft. 3. <u>5 1/4</u> ft.								
			WELL'S STATIC WATER LEVEL <u>50</u> ft. below land surface measured on mo/day/yr <u>5/14/95</u>								
			Pump test data: Well water was ft. after hours pumping gpm								
			Est. Yield <u>25</u> gpm Well water was ft. after hours pumping gpm								
			Bore Hole Diameter <u>10</u> in. to <u>80</u> ft. and in. to ft.								
			WELL WATER TO BE USED AS:								
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
			Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted								
			Water Well Disinfected? Yes <u>No</u>								
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded											
Blank casing diameter <u>4.5</u> in. to <u>60</u> ft. Dia in. to ft. Dia in. to ft.											
Casing height above land surface <u>12</u> in. weight lbs./ft. Wall thickness or gauge No. <u>540</u>											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>80</u> ft. From ft. to ft.											
GRAVEL PACK INTERVALS: From <u>25</u> ft. to <u>80</u> ft. From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Grout Intervals: From <u>3</u> ft. to <u>25</u> ft. From ft. to ft. From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage											
Direction from well? <u>West</u> How many feet? <u>150</u>											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		5		Earth							
5		12		brown clay							
12		65		yellow clay							
65		80		shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5/14/95</u> and this record is true to the best of my knowledge and belief. Kansas											
Water Well Contractor's License No. <u>493</u> This Water Well Record was completed on (mo/day/yr) <u>5/14/95</u>											
under the business name of <u>Reissner Well Drilling</u> by (signature) <u>Greg Reissner</u>											