

1 LOCATION OF WATER WELL:	FRACTION			Section Number	Township Number	Range Number
Butler	SW 1/4	SE 1/4	SE 1/4	20	T 27 S	R 3E EW
Distance and direction from nearest town or city street address of well if located within city?						
333 McCandless Andover, Kansas						
2 WATER WELL OWNER:	COMBS, W.J.			Board of Agriculture, Division of Water Resource		
RR#, ST. ADDRESS, BOX #:	333 McCandless			Application Number:		
CITY, STATE, ZIP CODE:	Andover, Kansas					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:						
4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 12 ft. FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 10/04/1995 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 50 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No						
5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:		Glued <input checked="" type="checkbox"/> Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	Welded			
2 PVC	4 ABS	7 Fiberglass	Threaded			
Blank casing Diameter 5 in. to 24 ft., Dia in. to ft., Dia in. to ft.						
casing height above land surface 12 in., weight 2.35 lbs. / ft.		7 PVC	Wall thickness or gauge No.		.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel	3 Stainless Steel	5 Fiberglass	10 Asbestos-cement			
2 Brass	4 Galvanized steel	6 Concrete tile	11 other (specify)			
SCREEN OR PERFORATION OPENING ARE:						
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	12 None used (open hole)		11 None (open hole)	
2 Louvered shutter	4 Key punched	6 Wire wrapped	13 Drilled holes			
SCREEN-PERFORATION INTERVALS: from 24 ft. to 50 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: from 24 ft. to 50 ft., From ft. to ft.						
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other		
Grout Intervals: From 4 ft. to 24 ft.		ft. From	ft. to	ft. From	ft. to	ft.
What is the nearest source of possible contamination:						
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens		14 Abandon water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage		16 Other (specify below)	
Direction from well?						
How many feet?						
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	4	topsoil				
4	15	clay				
15	50	shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/04/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10/05/95 Under the business name of Harp Well & Pump Service, Inc. by (signature)						