


1 LOCATION OF WATER WELL:		FRACTION			Section Number		Township Number		Range Number	
Butler		NE 1/4	NE 1/4	SE 1/4	19		T 27 S		R 3E EW	
Distance and direction from nearest town or city street address of well if located within city?										
257 Village Andover, Kansas										
2 WATER WELL OWNER:		BROWN, Craig			Board of Agriculture, Division of Water Resource					
RR#, ST. ADDRESS, BOX #:		257 Village			Application Number:					
CITY, STATE, ZIP CODE:		Andover, Kansas								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL 95 ft. ELEVATION:					
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.								
		WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 05/31/1996								
		Pump test data: Well water was ft. after hours pumping gpm								
		Est. Yield gpm: Well water was ft. after hours pumping gpm								
		Bore Hole Diameter 12 in. to 95 ft. and in. to ft.								
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)								
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted			Water Well Disinfected? Yes <input checked="" type="checkbox"/> No					
5 TYPE OF CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped								
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (Specify below)						Welded		
2 PVC 4 ABS		7 Fiberglass SDR-26 Threaded								
Blank casing Diameter 5 in. to 60 ft., Dia		in. to ft., Dia			in. to ft., Dia			in. to ft.		
Casing height above land surface 12 in., weight 2.35 lbs./ft.					7 PVC			Wall thickness or gauge No. 10 Asbestos-cement .214		
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass 8 RMP (SR)			11 other (specify)					
1 Steel 3 Stainless Steel		6 Concrete tile 9 ABS			12 None used (open hole)					
2 Brass 4 Galvanized steel										
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
1 Continous slot 3 Mill slot		6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 60 ft. to 95 ft., From ft. to ft.										
GRAVEL PACK INTERVALS: from 24 ft. to 95 ft., From ft. to ft.										
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.										
What is the nearest source of possible contamination:										
1 Septic tank 4 Lateral lines		7 Pit privy 10 Livestock pens 14 Abandon water well								
2 Sewer lines 5 Cess pool		8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well								
3 Watertight sewer lines 6 Seepage pit		9 Feedyard 12 Fertilizer storage 16 Other (specify below)								
10 Insecticide storage										
Direction from well? West					How many feet? 90					
FROM	TO	LITHOLOGIC LOG			FROM	TO	PLUGGING INTERVALS			
0	3	topsoil								
3	18	clay								
18	67	brown shale								
67	95	grey shale								
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/31/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 05/31/96. Under the business name of Harp Well & Pump Service, Inc. by (signature)									
										