

1 LOCATION OF WATER WELL:		Fraction <i>NW 1/4 NW 1/4 NW 1/4</i>	Section Number <i>30</i>	Township Number <i>T 27 S</i>	Range Number <i>R 3 E</i>
Distance and direction from nearest town or city street address of well if located within city? <i>Andover Kan 1/2 mile West</i>					
2 WATER WELL OWNER:		Linda Fraizer 517 Ruth Andover Kan 67020			
RR#, St. Address, Box #:		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code:		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>85</u> ft. ELEVATION: Depth(s) Groundwater Encountered <u>170</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>30</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>40</u> gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter <u>75</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) <input checked="" type="checkbox"/> PVC 4 ABS Blank casing diameter <u>5</u> in. to <u>30</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>18</u> in., weight <u>160</u> lbs./ft. Wall thickness or gauge No. <u>218</u>		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded PVC 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
6 SCREEN OR PERFORATION MATERIAL:		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut PVC 8 RMP (SR) 9 ABS 10 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched			
SCREEN-PERFORATED INTERVALS:		From. <u>30</u> ft. to <u>85</u> ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From. <u>0</u> ft. to <u>23</u> ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well <input checked="" type="checkbox"/> 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>W</u> How many feet? <u>100</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>4</u>	<i>Soil</i>			
<u>4</u>	<u>25</u>	<i>Clay</i>			
<u>25</u>	<u>85</u>	<i>Lime & Shale</i>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9/28/96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>251</u> This Water Well Record was completed on (mo/day/year) <u>7/4/96</u> by (signature) <u>Mark Winter</u>					