


1 LOCATION OF WATER WELL:		FRACTION		Section Number	Township Number	Range Number	
Butler		SE 1/4	NE 1/4	SE 1/4	19	T 27 S	R 3E EW
Distance and direction from nearest town or city street address of well if located within city?							
254 Village		Andover, Kansas					
WATER WELL OWNER: KLASING, Don		Board of Agriculture, Division of Water Resource					
RR#, ST. ADDRESS, BOX #: 254 Village		Application Number:					
CITY, STATE, ZIP CODE: Andover, Kansas							
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 97 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 08/30/1996 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 97 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No					
5 TYPE OF CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron	8 Concrete tile	CASING JOINTS:	
2 PVC		4 ABS		6 Asbestos-Cement	9 Other (Specify below)	Glued <input checked="" type="checkbox"/> Clamped	
Blank casing Diameter 5 in. to 27		ft., Dia		7 Fiberglass	SDR-26	Welded	
Casing height above land surface 12 in.,		weight 2.35		lbs. / ft.	Wall thickness or gauge No. 7 PVC	Threaded	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless Steel		5 Fiberglass	8 RMP (SR)	.214	
2 Brass		4 Galvanized steel		6 Concrete tile	9 ABS	10 Asbestos-cement	
SCREEN OR PERFORATION OPENING ARE:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter		4 Key punched		6 Wire wrapped	9 Drilled holes		
SCREEN-PERFORATION INTERVALS: from 27 ft. to 97 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: from 24 ft. to 97 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy	10 Livestock pens	ft. to ft.	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	11 Fuel storage	14 Abandon water well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	13 Insecticide storage	16 Other (specify below)	
Direction from well? North How many feet? 30							
FROM TO LITHOLOGIC LOG				FROM	TO	PLUGGING INTERVALS	
0	4	topsoil					
4	15	clay					
15	90	shale					
90	97	limestone					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/30/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/03/96							
Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Todd S. Harp</i>							