


1 LOCATION OF WATER WELL:		FRACTION SW 1/4	SE 1/4	SE 1/4	Section Number 19	T 27 s	Township Number R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 246 Village Andover, Kansas							
WATER WELL OWNER:		SHALON, Lionel					
RR#, ST. ADDRESS, BOX #:		246 Village					
CITY, STATE, ZIP CODE:		Andover, Kansas					
Board of Agriculture, Division of Water Resource		Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 97 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 09/09/1996					
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 97 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes submitted		No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was Water Well Disinfected? Yes <input checked="" type="checkbox"/> No					
5 TYPE OF CASING USED:		CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped 5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (Specify below) 7 Fiberglass SDR-26 Welded Threaded					
1 Steel 3 RMP (SR)							
2 PVC 4 ABS							
Blank casing Diameter 5 in. to 27 ft., Dia weight 2.35 lbs. / ft.		in. to ft., Dia in. to ft. Wall thickness or gauge No. .214 10 Asbestos-cement					
Casing height above land surface 12 in.,							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless Steel		5 Fiberglass 8 RMP (SR) 11 other (specify)					
2 Brass 4 Galvanized steel		6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENING ARE:							
1 Continuous slot 3 Mill slot		5 Gaused wrapped 8 Saw cut 6 Wire wrapped 9 Drilled holes 11 None (open hole)					
2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify)					
SCREEN-PERFORATION INTERVALS: from 27 ft. to 97 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: from 24 ft. to 97 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines		7 Pit privy 10 Livestock pens 14 Abandon water well					
2 Sewer lines 5 Cess pool		8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit		9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? East How many feet? 30							
FROM TO LITHOLOGIC LOG				FROM TO PLUGGING INTERVALS			
0	4	topsoil					
4	15	clay					
15	90	shale					
90	97	limestone					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) <u>reconstructed</u> , or (3) <u>plugged under my jurisdiction</u> and was completed on (mo/day/year) 09/09/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/10/96 . Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp							