


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County: <i>Butler</i>	NE $\frac{1}{4}$ SW $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 11	Township Number T 27 S	Range Number R 3 EW
Distance and direction from nearest town or city street address of well if located within city? <i>4 - W & 3 N of Augusta</i>						
2 WATER WELL OWNER:		<i>Steve Adkins 67213</i>				
RR#, St. Address, Box # :		<i>1920 Lydia Wichita Kan</i>				
City, State, ZIP Code		Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 105 ft. ELEVATION: 105				
		Depth(s) Groundwater Encountered 1. 85 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 20 gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 9.5 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/>				
5 TYPE OF BLANK CASING USED:		1 Steel <input checked="" type="checkbox"/> PVC	3 RMP (SR) <input checked="" type="checkbox"/> ABS	5 Wrought iron <input checked="" type="checkbox"/> PVC	8 Concrete tile <input checked="" type="checkbox"/> PVC	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input checked="" type="checkbox"/> Welded <input checked="" type="checkbox"/> Threaded <input checked="" type="checkbox"/>
Blank casing diameter		5 in. to ft.	Dia	in. to ft.	Dia	in. to ft.
Casing height above land surface		18 in.	weight	160 lbs./ft.	Wall thickness or gauge No.	1214
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)
SCREEN-PERFORATED INTERVALS:		From	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:		From	ft. to	ft., From	ft. to	ft.
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From	2 Cement grout ft. to	3 Bentonite ft. to	4 Other ft., From	ft. to ft.
What is the nearest source of possible contamination:		1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy <input checked="" type="checkbox"/> Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well?		W 150				
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	3	SOIL				
2	8	ROCK				
6	15	CLAY				
15	29	CLAY & SHALE				
27	105	1 SHALE				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:		This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <i>1/1999</i> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <i>2511997</i> This Water Well Record was completed on (mo/day/year) <i>1/1999</i> by (signature) <i>Charles Winter</i>				