


1 LOCATION OF WATER WELL:		FRACTION SE 1/4 SE 1/4 NE 1/4			Section Number 7	T 27 S	Range Number R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? <b>1747 N. Andover Road Andover, Kansas</b>							
WATER WELL OWNER:		ANDOVER MIDDLE SCHOOL			Board of Agriculture, Division of Water Resource		
RR#, ST. ADDRESS, BOX #:		1747 N. Andover Road			Application Number: 67002		
CITY, STATE, ZIP CODE :		Andover, Kansas					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 100 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 03/11/1997					
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 100 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
		Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> ; If yes, mo/day/yr sample was submitted			Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>		
5 TYPE OF CASING USED:		5 Wrought iron 8 Concrete tile Casing JOINTS: Glued <input checked="" type="checkbox"/> Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded 2 PVC 4 ABS 7 Fiberglass SDR-26 Threaded					
Blank casing Diameter 5 in. to 30 ft., Dia		in. to ft., Dia			in. to ft.		
Casing height above land surface 12 in., weight 2.35 lbs. / ft.					Wall thickness or gauge No. .214 10 Asbestos-cement		
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass 8 RMP (SR) 6 Concrete tile 9 ABS			11 other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
1 Continous slot 3 Mill slot		ft. to 100 ft. From ft. to ft.					
2 Louvered shutter 4 Key punched		ft. to ft. From ft. to ft.					
SCREEN-PERFORATION INTERVALS: from 30		ft. to 100 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: from 24		ft. to 100 ft. From ft. to ft.					
from		ft. to			ft. to		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout		3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 24 ft. From		ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandon water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			None Apparent		
Direction from well? How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	3	topsoil					
3	22	clay					
22	100	grey shale					
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/11/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 03/13/97 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Todd S. Harp</i>						