


1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 SE 1/4 SE 1/4	Section Number 19	Township Number T 27 S	Range Number R 3E E.W.			
Distance and direction from nearest town or city street address of well if located within city? 331 Village Andover, Kansas							
WATER WELL OWNER: FAHKHAUER, Rick	RR#, ST. ADDRESS, BOX #: 331 Village	Board of Agriculture, Division of Water Resource					
CITY, STATE, ZIP CODE: Andover, Kansas	Application Number:						
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL Depth(s) groundwater Encountered 95 ft.	ELEVATION: ft. below land surface measured on mo/day/yr 30 ft. 08/15/1997					
	Pump test data: Est. Yield gpm: 1 Bore Hole Diameter in. to 95	Well water was ft. after hours pumping gpm Well water was ft. after hours pumping gpm and in. to ft.					
	WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation	5 Public water supply 6 Oil field water supply 7 Lawn and garden only	8 Air conditioning 9 Dewatering 10 Monitoring well	11 Injection well 12 Other (Specify below)			
	Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>						
5 TYPE OF CASING USED: 1 Steel 2 PVC	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (Specify below)	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded				
Blank casing Diameter in. to 25	ft., Dia	in. to ft., Dia	in. to ft.				
Casing height above land surface in., weight 12 in., 2.35	lbs. / ft.	Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass							
3 Stainless Steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 other (specify) 12 None used (open hole)				
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 2 Louvered shutter							
3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)				
SCREEN-PERFORATION INTERVALS: from 25 ft. to 95 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: from ft. to ft. From ft. to ft. from ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 4 ft. to 24 ft. From	2 Cement grout	3 Bentonite	4 Other	bentonite hole plug			
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines	7 Pit privy 8 Sewage lagoon 9 Feedyard	ft. to ft. From ft. to ft.	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandon water well 15 Oil well/Gas well 16 Other (specify below)			
Direction from well? West	How many feet? 15						
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	4	topsoil					
4	20	clay					
20	95	shale					
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/15/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 08/18/97 . Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp						