

1 LOCATION OF WATER WELL: <b>Butler</b>		FRACTION <b>SW 1/4 NE 1/4 SW 1/4</b>	Section Number <b>19</b>	Township Number <b>T 27 S</b>	Range Number <b>R 3E E/W</b>
Distance and direction from nearest town or city street address of well if located within city? <b>245 S. Lakeside Andover, Kansas</b>					
WATER WELL OWNER: <b>ADIX, Dale</b>			Board of Agriculture, Division of Water Resource		
RR#, ST. ADDRESS, BOX #: <b>245 S. Lakeside</b>			Application Number:		
CITY, STATE, ZIP CODE: <b>Andover, Kansas</b>					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL <b>80</b> ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL <b>30</b> FT. BELOW LAND SURFACE MEASURED ON mo/day/yr <b>08/29/1997</b>			
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <b>12</b> in. to <b>80</b> ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <b>No</b> ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <b>X</b> No		
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (Specify below) 7 Fiberglass <b>SDR-26</b>	CASING JOINTS: Glued <b>X</b> Clamped Welded Threaded		
Blank casing Diameter <b>5</b> in. to <b>25</b> ft., Dia Casing height above land surface <b>12</b> in., weight <b>2.35</b> lbs. / ft.		in. to ft., Dia <b>7 PVC</b>	Wall thickness or gauge No. <b>.214</b> 10 Asbestos-cement		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel 5 Fiberglass 8 RMP (SR) 6 Concrete tile 9 ABS 11 other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut		8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)		
SCREEN-PERFORATION INTERVALS: from <b>25</b> ft. to <b>80</b> ft., From		ft. to	ft. to ft.		
GRAVEL PACK INTERVALS: from <b>24</b> ft. to <b>80</b> ft., From		ft. to	ft. to ft.		
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From <b>4</b> ft. to <b>24</b> ft. From		2 Cement grout ft. to	3 Bentonite ft. to	4 Other <b>bentonite hole plug</b> ft. From 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage <b>None Apparent</b>	ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 14 Abandon water well 15 Oil well/Gas well 16 Other (specify below)					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	4	<b>topsoil</b>			
4	15	<b>clay</b>			
15	80	<b>shale</b>			
PLUGGING INTERVALS					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) <u>reconstructed</u> , or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) <b>08/29/1997</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>236</b> This Water Well Record was completed on (mo/day/yr) <b>09/03/97</b> . Under the business name of <b>Harp Well &amp; Pump Service, Inc.</b> by (signature) <b>Todd S. Harp</b>					