


1 LOCATION OF WATER WELL: Butler		FRACTION NW 1/4 NW 1/4 NW 1/4				Section Number 9	Township Number T 27 S	Range Number R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 m. E. of Andover Rd. Southside of 21st N.								
WATER WELL OWNER: HOPE COMMUNITY CHURCH		Board of Agriculture, Division of Water Resource						
RR#, ST. ADDRESS, BOX #: 1831 E. 21st N.		Application Number:						
CITY, STATE, ZIP CODE: Andover, Kansas								
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 70 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft. below land surface measured on mo/day/yr 06/06/1997						
		WELL'S STATIC WATER LEVEL 38 ft. below land surface measured on mo/day/yr 06/06/1997						
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 70 ft. and in. to ft.						
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted						
		Water Well Disinfected? Yes <input checked="" type="checkbox"/> No						
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass SDR-26 Threaded						
Blank casing Diameter 5 in. to 40 ft., Dia in. to ft. weight 2.35 lbs. / ft. Wall thickness or gauge No. .214								
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214								
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel		5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 6 Concrete tile 9 ABS 11 other (specify) 7 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes						
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify)						
SCREEN-PERFORATION INTERVALS: from 40 ft. to 70 ft., From ft. to ft.								
GRAVEL PACK INTERVALS: from 24 ft. to 70 ft., From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout		3 Bentonite 4 Other						
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.		10 Livestock pens 14 Abandon water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below)						
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		13 Insecticide storage None Apparent						
Direction from well? West		How many feet? 15						
FROM 0 TO 3 LITHOLOGIC LOG topsoil		FROM 3 TO 15 PLUGGING INTERVALS						
15 42 broken shale								
42 70 grey shale								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/06/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/09/97 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp								