


1 LOCATION OF WATER WELL:			FRACTION			Section Number		Township Number		Range Number							
Butler			NE 1/4	SE 1/4	SE 1/4	1		T 27 s		R 3E E/W							
Distance and direction from nearest town or city street address of well if located within city?																	
1/4 N. of 21st N. & 1/8 W. of Santa Fe Lake Road Augusta, Kansas																	
WATER WELL OWNER: JOHNSON, Emmett RR#, ST. ADDRESS, BOX #: 11102 S.W. 65th CITY, STATE, ZIP CODE: Augusta, Kansas						Board of Agriculture, Division of Water Resource Application Number:											
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 127 ft. ELEVATION:														
			Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft. WELL'S STATIC WATER LEVEL 45 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 10/24/1998 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 127 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well														
Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> ; If yes, mo/day/yr sample was submitted			Water Well Disinfected? Yes <input checked="" type="checkbox"/> No														
5 TYPE OF CASING USED:																	
1 Steel 3 RMP (SR)			5 Wrought iron 8 Concrete tile			CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped											
2 PVC 4 ABS			6 Asbestos-Cement 9 Other (Specify below)			Welded											
Blank casing Diameter 5 in. to 47 ft., Dia			7 Fiberglass SDR - 26			Threaded											
Casing height above land surface 12 in., weight 2.35 lbs./ft.			8 PVC			Wall thickness or gauge No. 10 Asbestos-cement .214											
TYPE OF SCREEN OR PERFORATION MATERIAL:																	
1 Steel 3 Stainless Steel			5 Fiberglass			11 other (specify)											
2 Brass 4 Galvanized steel			6 Concrete tile 9 ABS			12 None used (open hole)											
SCREEN OR PERFORATION OPENING ARE:																	
1 Continous slot 3 Mill slot			5 Gauzed wrapped 8 Saw cut			11 None (open hole)											
2 Louvered shutter 4 Key punched			6 Wire wrapped 9 Drilled holes														
7 Torch cut 10 Other (specify)																	
SCREEN-PERFORATION INTERVALS: from 47 ft. to 127 ft., From ft. to ft.																	
from			ft. to			ft., From ft. to ft.											
GRAVEL PACK INTERVALS: from 24 ft. to 127 ft., From			ft. to			ft., From ft. to ft.											
from			ft. to			ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug																	
Grout Intervals: From 4 ft. to 24 ft. From			ft. to			ft. From ft. to ft.											
What is the nearest source of possible contamination:																	
1 Septic tank 4 Lateral lines			7 Pit privy			10 Livestock pens 14 Abandon water well											
2 Sewer lines 5 Cess pool			8 Sewage lagoon			11 Fuel storage 15 Oil well/Gas well											
3 Watertight sewer lines 6 Seepage pit			9 Feedyard			12 Fertilizer storage 16 Other (specify below)											
13 Insecticide storage																	
Direction from well? Northeast How many feet? 90																	
FROM			TO			LITHOLOGIC LOG			FROM			TO			PLUGGING INTERVALS		
0	2	topsoil															
2	15	rock															
15	127	shale															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/24/1998 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 10/26/98. Under the business name of Harp Well & Pump Service, Inc. by (signature)																	
												Todd S. Harp					