

WATER WELL RECORD

Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction C $\frac{1}{4}$ NE $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 17	Township Number T 27 S	Range Number R 3E E/W	
Distance and direction from nearest town or city street address of well if located within city? 707 Lakecrest Pl., Andover, KS						
2 WATER WELL OWNER:		Wendy Peterson RR#, St. Address, Box # : 707 Lakecrest Pl. City, State, ZIP Code : Andover, KS 67002				Board of Agriculture, Division of Water Resources Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 90 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 90 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted				Water Well Disinfected? Yes X No
5 TYPE OF BLANK CASING USED:		1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	CASING JOINTS: Glued X Clamped Welded Threaded		
Blank casing diameter		5 in. to 60	ft., Dia in. to ft., Dia in. to ft.	lbs./ft. Wall thickness or gauge No. SDR26		
Casing height above land surface		12 in., weight				
TYPE OF SCREEN OR PERFORATION MATERIAL:						7 PVC 10 Asbestos-cement 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:						5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 60 ft. to 90 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 20 ft. to 90 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout Grout Intervals: From 4 ft. to 20	3 Bentonite 4 Other			
What is the nearest source of possible contamination:						10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage
Direction from well?						How many feet?
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	18	Clay				
18	29	Shale				
29	34	Lime				
34	53	Shale				
53	83	Shale w/lime stks				
83	90	Cherty Lime				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/2/99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 171 This Water Well Record was completed on (mo/day/year) 9/12/99 under the business name of G & S Drilling, Inc.						by (signature)
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						