


1	LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SW 1/4 SW 1/4	Section Number 18	Township Number T 27 S	Range Number R 3E E/W		
Distance and direction from nearest town or city street address of well if located within city? 611 18th Fairway Andover, Kansas							
WATER WELL OWNER: DEFURIA, Carla RR#, ST. ADDRESS, BOX #: 611 18th Fairway CITY, STATE, ZIP CODE: Andover, Kansas			Board of Agriculture, Division of Water Resource Application Number:				
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 110 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 06/08/2000 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 110 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5	TYPE OF CASING USED:					CASING JOINTS: Glued X Clamped	
1	Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile			
2	PVC	4 ABS	6 Asbestos-Cement	9 Other (Specify below)	Welded		
	Blank casing Diameter 5 in. to 30	ft., Dia	7 Fiberglass	SDR - 26	Threaded		
	Casing height above land surface 12 in.,	weight 2.35	lbs. / ft.	7 PVC	Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1	Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 other (specify)		
2	Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)		
SCREEN OR PERFORATION OPENING ARE:							
1	Continous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
2	Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes			
			7 Torch cut	10 Other (specify)			
SCREEN-PERFORATION INTERVALS: from 30 ft. to 110 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: from 24 ft. to 110 ft., From ft. to ft.							
6	GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug						
Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1	Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well		
2	Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well		
3	Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)		
Direction from well? West How many feet? 20							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	3	topsoil					
3	17	clay					
17	65	brown shale					
65	110	grey shale					
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/08/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/09/00						
Under the business name of Harp Well & Pump Service, Inc. by (signature)							