


1 LOCATION OF WATER WELL:	Fraction	C $\frac{1}{4}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number	T 27 S	Range Number R 3E E/W		
County: Butler	Distance and direction from nearest town or city street address of well if located within city?						
2 WATER WELL OWNER: Darwin Folkerts	Board of Agriculture, Division of Water Resources						
RR#, St. Address, Box # : 712 N. 18 Fairway	Application Number:						
City, State, ZIP Code : Andover, KS 67002							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 100 ft. ELEVATION:						
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr C-6-01 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 100 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED:	1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped		
	2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded		
Blank casing diameter	5 in.	to 80 ft.	7 Fiberglass		Threaded		
Casing height above land surface	12 in.	weight			lbs./ft. Wall thickness or gauge No. 50R26		
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel	3 Stainless steel	5 Fiberglass	10 Asbestos-cement			
	2 Brass	4 Galvanized steel	6 Concrete tile	11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	3 Mill slot	5 Gauzed wrapped	12 None used (open hole)			
	2 Louvered shutter	4 Key punched	6 Wire wrapped	8 Saw cut 11 None (open hole)			
SCREEN-PERFORATED INTERVALS:	From 80 ft.	to 100 ft.	7 Torch cut	9 Drilled holes			
	From	ft. to	10 Other (specify)	ft. to			
GRAVEL PACK INTERVALS:	From 20 ft.	to 100 ft.	ft. From	ft. to			
	From	ft. to	ft. From	ft. to			
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other			
Grout Intervals:	From 4 ft.	to 20 ft.	ft. to	ft. From	ft. to		
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well		
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well		
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)		
Direction from well?	How many feet?						
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	22	clay					
22	32	shale					
32	38	lime					
38	58	shale w/ lime streaks					
58	76	lime					
76	100	cretaceous lime					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-6-01 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 171	This Water Well Record was completed on (mo/day/year) 6-23-01						
under the business name of G & S Drilling Inc.	by (signature) G & S Drilling Inc.						