

1	LOCATION OF WATER WELL: <i>Seagovin Butler</i>	FRACTION NW 1/4	SW SW SW NE <i>SW 1/4 1/4 SE 1/4</i>	Water Well Record Form WW-5 KSA 87a-1212	Section Number <i>SW 19</i>	Township Number <i>T 27 S</i>	Range Number <i>R 3 E</i> E/W
Distance and direction from nearest town or city street address of well if located within city? 115 S. Putter Andover, Kansas							
WATER WELL OWNER: HEAD, Dave RR#, ST. ADDRESS, BOX #: 115 S. Putter CITY, STATE, ZIP CODE: Andover, Kansas				Board of Agriculture, Division of Water Resource Application Number:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 85 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 6-19-2001 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 85 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>							
5	TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (Specify below) SDR-26	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded		
Blank casing Diameter 5 in. to 30		ft., Dia	in. to	ft., Dia	in. to	ft.	
Casing height above land surface 12 in.,		weight 2.35 lbs./ft.	7 PVC	Wall thickness or gauge No. .214 10 Asbestos-cement			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 other (specify) 12 None used (open hole)							
SCREEN OR PERFORATION OPENING ARE: 1 Continous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVALS: from 30 ft. to 85 ft., From ft. to ft. from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from 24 ft. to 85 ft., From ft. to ft. from ft. to ft., From ft. to ft.							
6	GROUT MATERIAL: 1 Neat cement Grout Intervals: From ft. to ft.		2 Cement grout ft. From ft. to ft.	3 Bentonite ft. From ft. to ft.	4 Other ft. From 4 ft. to 24 ft.	bentonite hole plug 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandon water well 15 Oil well/Gas well 16 Other (specify below)	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard How many feet? 80							
Direction from well? South				PLUGGING INTERVALS			
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	3	topsoil					
3	12	clay					
12	27	brown shale					
27	41	grey shale					
41	56	brown shale					
56	85	grey shale					
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-19-2001and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236This Water Well Record was completed on (mo/day/yr) 6-20-2001 Under the business name of..... Harp Well & Pump Service, Inc.by (signature) <i>Todd S. Harp</i>						