

1 LOCATION OF WATER WELL: Seagwick Butler		FRACTION NE 1/4 SW 1/4 SW 1/4		Section Number 18		Township Number T 27 S		Range Number R 3E E/W		
Distance and direction from nearest town or city street address of well if located within city? 1/4 N. of Central, E. of 159th E. Andover, Kansas										
WATER WELL OWNER: COX, Bill RR#, ST. ADDRESS, BOX #: 728 Fairway CITY, STATE, ZIP CODE: Andover, Kansas					Board of Agriculture, Division of Water Resource Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL 105 ft. ELEVATION:							
			Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.							
			WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 4-1-2002							
			Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 105 ft. and in. to ft.							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well										
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No										
5 TYPE OF CASING USED:										
1 Steel			3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued X Clamped	
2 PVC			4 ABS		6 Asbestos-Cement		9 Other (Specify below)		Welded	
Blank casing Diameter 5 in. to 40 ft., Dia			in. to ft.		7 Fiberglass		SDR-26		Threaded	
Casing height above land surface 12 in.,			weight 2.35 lbs./ft.		in. to ft.		Dia in. to ft.		Wall thickness or gauge No. .214	
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel			3 Stainless Steel		5 Fiberglass		8 RMP (SR)		11 other (specify)	
2 Brass			4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENING ARE:										
1 Continuous slot			3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter			4 Key punched		6 Wire wrapped		9 Drilled holes		10 Other (specify)	
SCREEN-PERFORATION INTERVALS:										
from 40 ft. to 105 ft., From			ft. to ft.		ft. to ft.		ft. to ft.		ft. to ft.	
GRAVEL PACK INTERVALS:			from 24 ft. to 105 ft., From		ft. to ft.		ft. to ft.		ft. to ft.	
6 GROUT MATERIAL:										
1 Neat cement			2 Cement grout		3 Bentonite		4 Other bentonite hole plug			
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft.										
What is the nearest source of possible contamination:										
1 Septic tank			4 Lateral lines		7 Pit privy		10 Livestock pens			
2 Sewer lines			5 Cess pool		8 Sewage lagoon		11 Fuel storage			
3 Watertight sewer lines			6 Seepage pit		9 Feedyard		12 Fertilizer storage			
							13 Insecticide storage			
14 Abandon water well										
15 Oil well/Gas well										
16 Other (specify below)										
Direction from well? South How many feet? 20										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-1-2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 4-3-2002										
Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp										