


1 LOCATION OF WATER WELL: Sedgeick BUTLER		FRACTION SW 1/4 NW 1/4 SE 1/4	Water Well Record Form WWC-5 KSA 87a-1212	Section Number 19	Township Number I 27 S	Range Number R 37 E
Distance and direction from nearest town or city street address of well if located within city? 239 S. Onewood Andover, Kansas						
WATER WELL OWNER: COBLE, Mick REPO. ST. ADDRESS, BOX #: 239 S. Onewood CITY, STATE, ZIP CODE: Andover, Kansas		Board of Agriculture, Division of Water Resource Application Number:				
LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 29 ft. BELOW LAND SURFACE MEASURED ON mo/day/yr 3-22-2002				
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 1.2 in. to 80 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No				
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought Iron 8 Concrete tile Casing JOINTS: Glued <input checked="" type="checkbox"/> Clamped 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass SDR-26 Threaded				
Blank casing Diameter 5 in. to 40 ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs. / ft.		Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel		7 PVC 10 Asbestos-cement 5 Fiberglass 8 RMP (SR) 6 Concrete tile 9 ABS 11 other (specify) 12 None used (open hole)				
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)				
SCREEN-PERFORATION INTERVALS: from 40 ft. to 80 ft., From ft. to ft. from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from 24 ft. to 80 ft., From ft. to ft. from ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard		3 Bentonite 4 Other bentonite hole plug ft. to ft. From ft. to ft. 10 Livestock pens 14 Abandon water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage				
Direction from well? East		How many feet? 80				
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	3	topsoil				
3	48	brown shale				
48	80	grey shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-22-2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 3-25-2002		Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp				