

1	LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 SE 1/4 NE 1/4	SECTION NUMBER 6	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
---	--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2727 N. Andover Rd. Andover, Kansas

2	WATER WELL OWNER:	HLADIK, Dale		
	RR#,ST. ADDRESS,BOX #:	16448 S.W. 150th		
	CITY, STATE:	Rosehill, Kansas	ZIP CODE:	

Board of Agriculture, Division of Water Resource

Application Number:

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N	4	DEPTH OF COMPLETED WELL: 82 ft.	ELEVATION:
		Depth of groundwater Encountered:	ft.	ft.

WELL'S STATIC WATER LEVEL **40** **FT. BELOW LAND SURFACE MEASURED ON** **4/15/03**

Pump test data: Well water was ft. after hours of pumping @ gpm

Est. Yield: gpm Well water was ft. after hours of pumping @ gpm

Bore Hole Diameter **12** in. to **82** ft. and in. to ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply

2. Irrigation 4. Industrial 6. Oil field water supply

7. Lawn and garden only 9. Dewatering 11. Injection well

8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES **NO** ; If yes, what mo/day/yr was sample submitted

Was Water Well Disinfected? YES **NO**

TYPE OF CASING USED:	CASING JOINTS:							
1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	<u>Glued</u>	Threaded		
<u>2. PVC</u>	4. ABS	6. Asbestos-Cement	8. Concrete tile		Welded	Clamped		
Blank casing diameter	5 in.	to	40 ft.,	Dia.	in.	to	ft.	
Casing height above land surface:	12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.	.214			
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1. Steel	3. Stainless Steel	5. Fiberglass	<u>7. PVC</u>	9. ABS	11. Other (specify)			
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:								
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)			
2. Louvered shutter	4. Key punched	6. Wire wrapped	<u>8. Saw cut</u>	10. Other (specify)				
SCREEN - PERFORATION INTERVAL	From	40 ft.	to	82 ft.,	From	ft.	to	ft.
		ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24 ft.	to	82 ft.,	From	ft.	to	ft.
		ft.	to	ft.,	From	ft.	to	ft.

6	GROUT MATERIALS:										
	1. Neat cement		2. Cement Grout		3. Bentonite		Other bentonite hole plug				
	Grout Intervals:	From 4 ft.	to 24 ft.,	From	ft.	to	ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:										
	1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well
	2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)
	3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage				
	Direction from well?		North						How many feet?		150

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. **constructed** 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **4-15-2003** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **4-16-2003**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *Jo dd S. Harp*