


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION SE 1/4 SW 1/4 SE 1/4	SECTION NUMBER 19	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city?								
2	WATER WELL OWNER: STRATTON, Robert	Board of Agriculture, Division of Water Resource						
RR#, ST. ADDRESS, BOX #: 354 Pitchers Ct.		CITY, STATE: Andover, Kansas		ZIP CODE:	Application Number:			
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4	DEPTH OF COMPLETED WELL: 82 ft.	ELEVATION:				
		Depth of groundwater Encountered: ft. ft. ft.						
		WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr:	5/28/04					
		Pump test data: Well water was	ft. after	hours of pumping @	gpm			
		Est. Yield: gpm Well water was	ft. after	hours of pumping @	gpm			
		Bore Hole Diameter 12 in. to 82 ft. and in. to ft.						
		WELL WATER TO BE USED AS:						
		1. Domestic 3. Feedlot 5. Public water supply	7. Lawn and garden only	9. Dewatering	11. Injection well			
		2. Irrigation 4. Industrial 6. Oil field water supply	8. Air conditioning	10. Monitoring well	12. Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department?	YES	NO	Was a chemical/bacteriological sample submitted to Department?			
			Was Water Well Disinfected?	YES	NO			
5	TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS: Glued	Threaded		
	1. Steel 3. RPM (SR)	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded	Clamped		
	2. PVC 4. ABS							
	Blank casing diameter 5 in. to 42 ft. Dia.	in. to	ft. Dia.	in. to	ft.			
	Casing height above land surface: 24 in., Weight: 2.35 lbs. / ft.				Wall thickness or gauge No. .214			
	TYPE OF SCREEN OR PERFORATION MATERIAL:	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)			
	1. Steel 3. Stainless Steel	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)			
	2. Brass 4. Galvanized							
	SCREEN OR PERFORATION OPENINGS ARE:							
	1. Continuous slot 3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)			
	2. Louvered shutter 4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)				
	SCREEN - PERFORATION INTERVAL From 42 ft. to 82 ft.	From 42 ft. to 82 ft.	From 42 ft. to 82 ft.	From 42 ft. to 82 ft.	From 42 ft. to 82 ft.			
	GRAVEL PACK INTERVALS: From 24 ft. to 82 ft.	From 24 ft. to 82 ft.	From 24 ft. to 82 ft.	From 24 ft. to 82 ft.	From 24 ft. to 82 ft.			
6	GROUT MATERIALS:	1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug		
	Grout Intervals: From 4 ft. to 24 ft.	From 4 ft. to 24 ft.	From 4 ft. to 24 ft.	From 4 ft. to 24 ft.	From 4 ft. to 24 ft.	From 4 ft. to 24 ft.		
	What is the nearest source of possible contamination:							
	1. Septic tank 4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well			
	2. Sewer lines 5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)			
	3. Watertight sewer line 6. Seepage pit	9. Feed yard	12. Fertilizer storage					
	Direction from well? East	How many feet? 15						
	From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
	0	3	topsoil					
	3	10	clay					
	10	50	tan clay					
	50	80	gray shale					
	80	82	gypsum-limestone					
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and							
	was completed on (mo/day/year) 5/28/2004	and this record is true to the best of my knowledge and belief.						
	Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 5/31/2004						
	under the business name of Harp Well & Pump Service Inc.	by (signature) 