


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SE 1/4 NE 1/4	SECTION NUMBER 18	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 14001 N.S. 10th Andover, Kansas							
2 WATER WELL OWNER: HESSEY, Tom	RR#, ST. ADDRESS, BOX #: 14001 N.S. 10th	Board of Agriculture, Division of Water Resource					
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 65 ft.	ELEVATION: ft.					
Depth of groundwater Encountered: ft.		ft.		ft.			
WELL'S STATIC WATER LEVEL Pump test data: Est. Yield: gpm Bore Hole Diameter 12 in.	15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/20/04	ft. after	hours of pumping @	gpm			
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply Was a chemical/bacteriological sample submitted to Department? submitted	7. Lawn and garden only	ft. after	hours of pumping @	gpm			
	9. Dewatering	11. Injection well					
	10. Monitoring well	12. Other (Specify below)					
	YES	NO	Was sample				
	Was Water Well Disinfected?	YES	NO				
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Welded	Threaded Clamped		
Blank casing diameter 5 in.	to 23 ft.	Dia.	in. to ft.	Dia.	in. to ft.		
Casing height above land surface: 12 in.	Weight: 2.35 lbs. / ft.			Wall thickness or gauge No.	.214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC 8. RMP (SR)	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)				
SCREEN - PERFORATION INTERVAL From 23 ft. to 65 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,		
GRAVEL PACK INTERVALS: From 23 ft. to 65 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,		
6 GROUT MATERIALS: Grout Intervals: From 3 ft. to 23 ft.,	2. Cement Grout 7. Pit privy	3. Bentonite 10. Livestock pens	Other 13. Insecticide storage	bentonite hole plug 15. Oil well/Gas well			
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit	8. Sewage lagoon 9. Feed yard	11. Fuel storage 12. Fertilizer storage	14. Abandon water well	16. Other (specify below)			
Direction from well? West	How many feet? 200						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	4	topsoil					
4	15	clay					
15	33	medium sand					
33	65	shale					
RECEIVED							
OCT 07 2004							
BUREAU OF WATER							
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/20/2004 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/22/2004							
under the business name of Harp Well & Pump Service Inc. by (signature) Jodd S. Harp							