


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SE SW 1/4 SW 1/4 NE 1/4	SECTION NUMBER 19	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W	
Distance and direction from nearest town or city street address of well if located within city? 604 Dog Leg Ct. Andover, Kansas					
2 WATER WELL OWNER: TODD, Mark	RR#ST. ADDRESS, BOX #: 604 Dog Leg Ct.	Board of Agriculture, Division of Water Resource			
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 82 ft.	ELEVATION: ft. ft. ft.			
1 Mile	Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL Pump test data: Est. Yield: gpm Bore Hole Diameter 12 in.	20	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 8/26/04		
	Well water was ft. after hours of pumping @ gpm	Well water was ft. after hours of pumping @ gpm	and in. to ft.		
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? YES NO Was Water Well Disinfected? YES NO	9. Dewatering 11. Injection well 12. Other (Specify below)	; If yes, what mo/day/yr was sample		
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC Blank casing diameter 5 in.	5. Wrought Iron 4. ABS to 42 ft., Dia.	7. Fiberglass 6. Asbestos-Cement 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Welded	Threaded Clamped
Casing height above land surface: 12 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)					
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)					
SCREEN - PERFORATION INTERVAL		From 42 ft.	to 82 ft.,	From	ft. to ft.
GRAVEL PACK INTERVALS:		From 24 ft.	to 82 ft.,	From	ft. to ft.
6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 4. Lateral lines 5. Cess Pool 6. Seepage pit	2. Cement Grout 7. Pit privy 8. Sewage lagoon 9. Feed yard	3. Bentonite 10. Livestock pens 11. Fuel storage 12. Fertilizer storage	Other 13. Insecticide storage 14. Abandon water well	bentonite hole plug 15. Oil well/Gas well 16. Other (specify below)
What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line Direction from well? West	How many feet? 20				
LITHOLOGIC LOG					
From 0	To 4	topsoil	From	To	LITHOLOGIC LOG
4	15	clay			
15	82	shale			
RECEIVED					
SEP 24 2004					
BUREAU OF WATER					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 8/26/2004 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/30/2004					
under the business name of Harp Well & Pump Service Inc.			by (signature) <i>Todd S. Harp</i>		