


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4	SE 1/4	NW 1/4	SECTION NUMBER 19	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 908 W. Putter Andover, Kansas						
2 WATER WELL OWNER: Edmundson, Joe	Board of Agriculture, Division of Water Resource					
RR#, ST. ADDRESS, BOX #: 908 W. Putter	CITY, STATE: Andover, Kansas					ZIP CODE: Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 82	ft.	ELEVATION:			
	Depth of groundwater Encountered:	ft.	ft.			
	WELL'S STATIC WATER LEVEL 30	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr:	9/27/04		
	Pump test data: Est. Yield: 12 gpm	Well water was	ft. after	hours of pumping @	gpm	
	Bore Hole Diameter 12 in.	Well water was	ft. after	hours of pumping @	gpm	
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? submitted					
	9. Dewatering 11. Injection well 10. Monitoring well Was Water Well Disinfected? YES NO ; If yes, what mo/day/yr was sample					
5 TYPE OF CASING USED: 1. Steel 2. PVC 3. RPM (SR) 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below)	CASING JOINTS: SDR-26	Glued Welded	Threaded Clamped
Blank casing diameter 5 in.	to 42 ft.	Dia.	in. to	ft., Dia.	in. to	ft.
Casing height above land surface: 12 in.		Weight: 2.35 lbs. / ft.		Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)						
11. Other (specify)						
12. None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)						
SCREEN - PERFORATION INTERVAL From 42 ft. to 82 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 24 ft. to 82 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIALS: 1. Neat cement Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	2. Cement Grout 7. Pit privy 8. Sewage lagoon 9. Feed yard	3. Bentonite 10. Livestock pens 11. Fuel storage 12. Fertilizer storage	Other	bentonite hole plug		
What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line	4. Lateral lines 5. Cess Pool 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)	
Direction from well?: West	How many feet? 95					
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG
0	4	topsoil				
4	15	clay				
15	82	shale				
RECEIVED						
OCT 19 2004						
BUREAU OF WATER						
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/27/2004 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 9/29/2004					
under the business name of Harp Well & Pump Service Inc.	by (signature) <i>Jodd S. Harp</i>					