


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SE 1/4 NW 1/4 SE 1/4	SECTION NUMBER 19	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W	
Distance and direction from nearest town or city street address of well if located within city? 206 S. Onewood Andover, Kansas					
2 WATER WELL OWNER: WOOD, Jeana	RR#, ST. ADDRESS, BOX #: 206 S. Onewood	Board of Agriculture, Division of Water Resource			
CITY, STATE: Andover, Kansas		ZIP CODE:	Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 82 ft.	ELEVATION: ft. ft. ft.			
Depth of groundwater Encountered: ft. ft. ft.					
WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/30/04					
Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm					
Bore Hole Diameter 12 in. to 82 ft. and in. to ft.					
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO					
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) Casing Joints: Glued Threaded 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped					
Blank casing diameter 5 in. to 32 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)					
SCREEN - PERFORATION INTERVAL From 32 ft. to 82 ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 82 ft., From ft. to ft., From ft. to ft.					
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? South	How many feet? 20				
LITHOLOGIC LOG					
From 0 To 4 topsoil	From	To	LITHOLOGIC LOG		
From 4 To 15 clay	From	To			
From 15 To 82 shale	From	To			
RECEIVED OCT 19 2004					
BUREAU OF WATER					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/30/2004 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 10/4/2004				
under the business name of Harp Well & Pump Service Inc.	by (signature) 