


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 NW 1/4 NW 1/4	SECTION NUMBER 7	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1912 N. 159th Andover, Kansas				
2 WATER WELL OWNER: MC AMMIE, Bob	RR#, ST. ADDRESS, BOX #: 1912 N. 159th	Board of Agriculture, Division of Water Resource		
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 125 ft.	ELEVATION: ft. ft. ft.		
Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL	70 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/21/04			
Pump test data: Est. Yield: gpm	Well water was Well water was	ft. after ft. after	hours of pumping @ hours of pumping @	gpm gpm
Bore Hole Diameter 12 in.	to 125 ft.	and	in. to	ft.
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO	12. Other (Specify below)			
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped				
Blank casing diameter 5 in. to 70 ft., Dia. in. to ft., Dia. in. to ft.				
Casing height above land surface: 24 in., Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 70 ft. to 125 ft., From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 24 ft. to 125 ft., From ft. to ft., From ft. to ft.				
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
Direction from well? Northeast How many feet? 150				
From To LITHOLOGIC LOG	From	To	LITHOLOGIC LOG	
0 4 topsoil				
4 30 clay				
30 120 shale				
120 125 limestone				
RECEIVED				
NOV 01 2004				
BUREAU OF WATER				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/21/2004 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 10/25/2004			
under the business name of Harp Well & Pump Service Inc.	by (signature) J. d. S. Harp			