

| | | | | | |
|--|---|---|--|---|---|
| 1 | LOCATION OF WATER WELL: County: | Fraction 1/4 1/4 1/4 | Section Number 19 | Township Number T 270 R 36 S 36 | Range Number 36 |
| Distance and direction from nearest town or city street address of well if located within city 105 W. Putter Circle - Andover | | | | | |
| 2 | WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code | Treescape | | | |
| Board of Agriculture, Division of Water Resources Application Number: | | | | | |
| 3 | LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N - - NW - - - NE - - W X E - - SW - - - SE - - S | 4 | DEPTH OF COMPLETED WELL 89 | ft. ELEVATION: ft. 3 Depth(s) Groundwater Encountered ft. 2 ft. 3 WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 12-15-04 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 12 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well | |
| Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No | | | | | |
| 5 | TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS | 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass | 8 Concrete tile 9 Other (specify below) | CASING JOINTS: Glued Clamped Welded Threaded | |
| Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 240 lbs./ft. Wall thickness or guage No. 100psi | | | | | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 9 ABS 11 Other (Specify) 12 None used (open hole) | | | | | |
| SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Glazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft. | | | | | |
| SCREEN-PERFORATED INTERVALS: From 21 ft. to 89 ft., From ft. to ft. From ft. to 89 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 25 ft. to 89 ft., From ft. to ft. From ft. to 89 ft., From ft. to ft. | | | | | |
| 6 | GROUT MATERIAL: 1 Neat cement Grout Intervals: From 3 ft. to 250 ft., From ft. to ft., From ft. to ft. | 2 Cement grout | 3 Bentonite | 4 Other 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage | 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) |
| What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard How many feet? | | | | | |
| FROM | TO | LITHOLOGIC LOG 0 10 20 30 topsoil 2 10 clay 10 65 limestone 65 89 shale | FROM | TO | PLUGGING INTERVALS |

| | |
|---|--|
| 7 | CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-15-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318-3105 This Water Well Record was completed on (mo/day/yr) 1-1-05 by (signature) <i>Wingate Drilling Inc. Outlines Drills</i> |
|---|--|