


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SW 1/4 NW 1/4	SECTION NUMBER 20	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W		
Distance and direction from nearest town or city street address of well if located within city? 840 Sunset Circle Andover, Kansas						
2 WATER WELL OWNER: BEERS, Chet	RR#, ST. ADDRESS, BOX #: 840 Sunset Circle	Board of Agriculture, Division of Water Resource				
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 96 ft.	ELEVATION: Depth of groundwater Encountered: ft. ft.	ft.			
		WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 4/7/05				
1 Mile	Pump test data: Est. Yield: gpm	Well water was Well water was	ft. after ft. after	hours of pumping @ gpm		
	Bore Hole Diameter 12 in.	to 96 ft.	and in.	to ft.		
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply	7. Lawn and garden only	9. Dewatering 10. Monitoring well	11. Injection well 12. Other (Specify below)		
	Was a chemical/bacteriological sample submitted to Department? submitted	YES NO	Was Water Well Disinfected? YES	; If yes, what mo/day/yr was sample		
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Welded	Threaded Clamped
	Blank casing diameter 5 in.	to 31 ft.	Dia.	in. to ft.	Dia.	in. to ft.
	Casing height above land surface: 12 in.	Weight: 2.35 lbs. / ft.			Wall thickness or gauge No.	.214
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC 8. RMP (SR)	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)		
	SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)		
	SCREEN - PERFORATION INTERVAL From 31 ft. to 96 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.		
	GRAVEL PACK INTERVALS: From 24 ft. to 96 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.		
6	GROUT MATERIALS: 1. Neat cement Grout Intervals: From 4 ft. to 24 ft.	2. Cement Grout From ft. to ft.	3. Bentonite ft. to ft.	Other bentonite hole plug		
	What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)	
	Direction from well? South	How many feet? 50				
	From To LITHOLOGIC LOG	From To	LITHOLOGIC LOG			
0	3 topsoil					
3	10 clay					
10	30 tan shale					
30	70 gray shale					
70	96 black shale-gypsum-limestone					
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/7/2005					and this record is true to the best of my knowledge and belief.
	Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 4/11/2005				
	under the business name of Harp Well & Pump Service Inc.	by (signature) 