


WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL:		FRACTION SE 1/4 SW 1/4 NW 1/4				SECTION NUMBER 29	TOWNSHIP NUMBER T 27 S			RANGE NUMBER R 3E E/W					
Distance and direction from nearest town or city street address of well if located within city?															
1/4 mile South of 54, 1/8 mile East of Andover Road										Andover, Kansas					
WATER WELL OWNER:		ADAMS, Dean 713 Westview Circle Andover, Kansas				Board of Agriculture, Division of Water Resource Application Number:									
RR#, ST. ADDRESS, BOX #:															
CITY, STATE:						ZIP CODE:									
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 76 ft. ELEVATION:													
		Depth of groundwater Encountered: ft. ft. ft.													
		WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/21/05													
		Pump test data: Well water was ft. after hours of pumping @ gpm													
		Est. Yield: gpm Well water was ft. after hours of pumping @ gpm													
		Bore Hole Diameter 12 in. to 76 ft. and in. to ft.													
		WELL WATER TO BE USED AS:													
		1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well													
		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well													
		Was a chemical/bacteriological sample submitted to Department? YES 12. Other (Specify below)													
		Was Water Well Disinfected? YES ; If yes, what mo/day/yr was sample NO													
TYPE OF CASING USED:		5. Wrought Iron 7. Fiberglass 9. Other (Specify below)				CASING JOINTS: 13. Glued		Threaded							
1. Steel 2. PVC		3. RPM (SR) 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26				Welded		Clamped							
Blank casing diameter		5	in.	to	36	ft.	Dia.	in.	to	ft.	Dia.	in.	to	ft.	
Casing height above land surface:		24	in.	Weight: 2.35 lbs. / ft.			Wall thickness or gauge No. .214								
TYPE OF SCREEN OR PERFORATION MATERIAL:															
1. Steel 2. Brass		3. Stainless Steel 4. Galvanized		5. Fiberglass 7. PVC		9. ABS 10. Asbestos-Cement		11. Other (specify) 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:															
1. Continuous slot 2. Louvered shutter		3. Mill slot 4. Key punched		5. Gauzed wrapped 6. Wire wrapped		7. Torch cut 8. Saw cut		9. Drilled holes 10. Other (specify)		11. None (open hole)					
SCREEN - PERFORATION INTERVAL		From 36 ft.		to 76 ft.		From		ft.		to ft.					
GRAVEL PACK INTERVALS:		From ft.		to 76 ft.		From		ft.		to ft.					
From ft.		to ft.		From		ft.		ft.		to ft.					
GROUT MATERIALS:		1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug					
Grout Intervals:		From 4 ft.		to 24 ft.		From ft.		to ft.		From ft.		to ft.			
What is the nearest source of possible contamination:															
1. Septic tank 3. Watertight sewer line		4. Lateral lines 6. Seepage pit		7. Pit privy 9. Feed yard		10. Livestock pens 12. Fertilizer storage		13. Insecticide storage 14. Abandon water well		15. Oil well/Gas well 16. Other (specify below)					
Direction from well? West How many feet? 50 feet plus															
From		To		LITHOLOGIC LOG				From		To		LITHOLOGIC LOG			
0	3	topsoil													
3	7	clay													
7	35	tan shale													
35	60	gray shale													
60	76	gypsum-black shale-limestone													
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and															
was completed on (mo/day/year)		7/21/2005		and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No.		236		This water well record was completed on (mo/day/year) 7/22/2005											
under the business name of Harp Well & Pump Service Inc. by (signature) 															