

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>		<u>SW 1/4 SW 1/4 NE 1/4</u>	<u>27</u>	<u>T 27 S</u>	<u>R 3 E/W</u>

Distance and direction from nearest town or city street address of well if located within city?
1 mile south of Andover, 2 miles East on north side

2 WATER WELL OWNER: <u>Bruce Green</u>		Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box # : <u>2626 E. Harry St</u> City, State, ZIP Code : <u>Andover, KS 67002</u>		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>104</u> ft. ELEVATION:	
--	--	---	--

Depth(s) Groundwater Encountered 1 8.5 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 35 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
<input checked="" type="radio"/> PVC	4 ABS	7 Fiberglass		Threaded

Blank casing diameter 5 in. to ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	<input checked="" type="radio"/> PVC	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	<input checked="" type="radio"/> Mill slot	5 Guazed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 84 ft. to 104 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 104 ft., From ft. to ft.

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	<input checked="" type="radio"/> Bentonite	4 Other
-------------------	--	---------------	----------------	--	---------

Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
<input checked="" type="radio"/> Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? How many feet? 50 ft

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>4</u>	<u>earth</u>			
<u>4</u>	<u>12</u>	<u>red clay</u>			
<u>12</u>	<u>15</u>	<u>green shale</u>			
<u>15</u>	<u>20</u>	<u>yellow clay</u>			
<u>20</u>	<u>104</u>	<u>shale lime</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>943</u> This Water Well Record was completed on (mo/day/yr) under the business name of <u>Reisner Well Drilling</u> by (signature) <u>Jerry Reisner</u>	
---	--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health.