

## Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Butler Fraction: NW 1/4 NW 1/4 NW 1/4 Section Number: 7 Township Number: T 27 S Range Number: R 3 E

Distance and direction from nearest town or city street address of well if located within city? 1709 N. Peartree Ct.

2 WATER WELL OWNER: Jim Ohmart  
RR#, St. Address, Box # : 1709 N. Peartree Ct.  
City, State, ZIP Code : Andover, KS

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
-- NW --	-- NE --
W	E
-- SW --	-- SE --
S	

4 DEPTH OF COMPLETED WELL: 90 ft.

Depth(s) Groundwater Encountered (1) 33 ft. (2) \_\_\_\_\_ ft. (3) \_\_\_\_\_ ft.

WELL'S STATIC WATER LEVEL: 33 ft. below land surface measured on 9/7/05

Pump test data: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm

Est. Yield \_\_\_\_\_ gpm: Well water was \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No X; If yes, mo/day/yr \_\_\_\_\_

Sample was submitted \_\_\_\_\_ Water well disinfected? Yes X No \_\_\_\_\_

5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped \_\_\_\_\_

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded \_\_\_\_\_

2 PVC 4 ABS 7 Fiberglass Threaded \_\_\_\_\_

Blank casing diameter 5 in. to 90 ft. Diameter \_\_\_\_\_ in. to \_\_\_\_\_ ft. Diameter \_\_\_\_\_ in. to \_\_\_\_\_ ft.

Casing height above land surface 16 in. weight 160 lbs./ft. Wall thickness or gauge No. 26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) \_\_\_\_\_

2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) \_\_\_\_\_

SCREEN-PERFORATED INTERVALS: From 50 ft. to 90 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

GRAVEL PACK INTERVALS: From 24 ft. to 90 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other \_\_\_\_\_

Grout Intervals: From 4 ft. to 24 ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft. From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil wll/gas well

Direction from well? North How many feet? 40

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0	2	topsoil			
2	9	green shale			
9	33	blue shale			
33	41	limestone			
41	90	blue shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/7/05 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 6611 This Water Well Recored was completed on (mo/day/year) 9/25/05

Under the business name of Chase Drilling by (signature) F. Chase

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.