


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler		FRACTION SE 1/4 NW 1/4 NW 1/4	SECTION NUMBER 19	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1422 Chaumont Circle Andover, Kansas					
2 WATER WELL OWNER: CARPENTER, Shawn RR#, ST. ADDRESS, BOX #: 1422 Chaumont Circle CITY, STATE: Andover, Kansas		Board of Agriculture, Division of Water Resource			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 11/5/05 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 80 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES 12. Other (Specify below) submitted NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO			
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped Blank casing diameter 5 in. to 35 ft. Dia. in. to ft. Dia. in. to ft.		Casing height above land surface: 24 in. Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)					
SCREEN - PERFORATION INTERVAL		From 35 ft. to 80 ft.,	From	ft.	to ft.
GRAVEL PACK INTERVALS:		From 24 ft. to 80 ft.,	From	ft.	to ft.
From ft. to ft. ,		From	ft.	to ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug		From ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft.			
Grout Intervals: From 4 ft. to 24 ft.,		From ft. to ft.,			
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well?: South		How many feet? 80 feet plus			
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 11/05/2005 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236		This water well record was completed on (mo/day/year) 11/07/05			
under the business name of Harp Well & Pump Service Inc.		by (signature) <i>Todd S. Harp</i>			