


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SE 1/4 SE 1/4 NW 1/4	SECTION NUMBER 7	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1750 Black Locust Andover, Kansas				
2 WATER WELL OWNER: KLAUSMEYER CONSTRUCTION	RR#, ST. ADDRESS, BOX #: 10008 W. York	Board of Agriculture, Division of Water Resource		
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 100 ft.	ELEVATION: ft. ft. ft.		
Depth of groundwater Encountered:				
WELL'S STATIC WATER LEVEL Pump test data: Est. Yield: gpm	35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 12/28/05	Well water was	ft. after	hours of pumping @ gpm
Bore Hole Diameter 12 in.		Well water was	ft. after	hours of pumping @ gpm
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only	100 ft.	and	in. to ft.	
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning				
Was a chemical/bacteriological sample submitted to Department? submitted	YES	NO	9. Dewatering 11. Injection well	
			10. Monitoring well 12. Other (Specify below)	
			Was Water Well Disinfected? YES NO	
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) Casing joints: 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Glued Welded Threaded Clamped				
Blank casing diameter 5 in. to 40 ft., Dia. in. to ft., Dia. in. to ft.				
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft.			Wall thickness or gauge No. .214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 40 ft. to 100 ft., From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 24 ft. to 100 ft., From ft. to ft., From ft. to ft.				
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug				
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
Direction from well?: West How many feet? 50 feet plus				
From To LITHOLOGIC LOG	From To	LITHOLOGIC LOG		
0 3 topsoil				
3 10 clay				
10 45 tan shale				
45 100 gray shale-limestone				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 12/28/2005 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 12/30/2005			
under the business name of Harp Well & Pump Service Inc.	by (signature) <i>Todd S. Harp</i>			