


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 SW 1/4 SW 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 620 Brentwood Ct. Andover, Kansas							
2 WATER WELL OWNER: NG, Derek	RR#, ST. ADDRESS, BOX #: 620 Brentwood Ct.	Board of Agriculture, Division of Water Resource					
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 80 ft.	ELEVATION: ft. ft. ft.					
	Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 2/27/06						
1 Mile	Pump test data: Est. Yield: gpm	Well water was ft. after	hours of pumping @ ft. after	gpm			
	Bore Hole Diameter 12 in.	to 80 ft.	and	in. to ft.			
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply Was a chemical/bacteriological sample submitted to Department?	7. Lawn and garden only	9. Dewatering 10. Monitoring well	11. Injection well 12. Other (Specify below)			
	YES	NO	; If yes, what mo/day/yr was sample				
		Was Water Well Disinfected?	YES	NO			
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC	5. Wrought Iron 4. ABS	7. Fiberglass 6. Asbestos-Cement	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Welded	Threaded Clamped		
Blank casing diameter 5 in.	to 40 ft.	Dia.	in. to	ft., Dia.	in. to ft.		
Casing height above land surface: 24 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile							
7. PVC	9. ABS 8. RMP (SR)	10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped							
7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)					
SCREEN - PERFORATION INTERVAL From 40 ft. to 80 ft.	From 40 ft. to 80 ft.	From ft. to ft.					
From ft. to ft.	From ft. to ft.	From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 80 ft.							
From ft. to ft.	From ft. to ft.	From ft. to ft.					
6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 2. Cement Grout	3. Bentonite	Other	bentonite hole plug			
What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line	4. Lateral lines 5. Cess Pool 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)		
Direction from well? West	How many feet? 50 feet plus						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	topsoil					
3	10	clay					
10	35	tan shale					
35	70	gray shale					
70	80	gray shale/limestone					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 2/27/2006 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 3/1/2006						
under the business name of Harp Well & Pump Service Inc.	by (signature) 