

1 LOCATION OF WATER WELL:		FRACTION SE 1/4 NE 1/4 NW 1/4			Section Number 31	Township Number T 27 S	Range Number R 3E E/W
Distance and direction from nearest town or city street address of well if located within city?							
1/2 E. of 159th E., 1/4 S. of Harry Wichita, Kansas							
2 WATER WELL OWNER:		BULLINS, Jim			Board of Agriculture, Division of Water Resource		
RR#, ST. ADDRESS, BOX #:		1738 Heatherlake Ct.			Application Number:		
CITY, STATE, ZIP CODE:		Wichita, Kansas					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL 17 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 06/09/1993 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 50 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No							
5 TYPE OF CASING USED:							
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS:		Glued <input checked="" type="checkbox"/> Clamped	
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (Specify below)	Welded			
Blank casing Diameter 5 in. to 50 ft., Dia		7 Fiberglass		SDR-26		Threaded	
Casing height above land surface 12 in., weight 2.35 lbs. / ft.		7 PVC		Wall thickness or gauge No. 10 Asbestos-cement		.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 other (specify)			
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:							
1 Continous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)			
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes				
7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVALS: from 25 ft. to 50 ft., From ft. to ft.							
from ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: from 24 ft. to 50 ft., From ft. to ft.							
from ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
13 Insecticide storage							
Direction from well? North How many feet? 55							
FROM TO LITHOLOGIC LOG				FROM TO PLUGGING INTERVALS			
0	3	topsoil					
3	13	clay					
13	38	brown shale					
38	50	grey shale					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/09/1993 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 06/15/93.

Well Contractor's License No. This Water Well Record was completed on (no/day)
Under the business name of **Harp Well & Pump Service, Inc.** by (signature)

Jane Frederick