


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: <i>Sedgewick BUTLER</i>	FRACTION NE NW SE 1/4 SE 1/4	SECTION NUMBER 31	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3 E E/W		
Distance and direction from nearest town or city street address of well if located within city? 224 W. Tuscany Place Andover, Kansas						
2 WATER WELL OWNER: CARDENA, Amy	RR# ST. ADDRESS, BOX #: 224 W. Tuscany Place	Board of Agriculture, Division of Water Resource				
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 70 ft.	ELEVATION: ft. ft. ft.				
	Depth of groundwater Encountered:					
	WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 3/7/06					
	Pump test data: Est. Yield: gpm	Well water was ft. after	hours of pumping @ ft. after	gpm		
	Bore Hole Diameter 12 in.	to 70 ft.	and	in. to ft.		
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? submitted	9. Dewatering YES	11. Injection well NO	12. Other (Specify below) ; If yes, what mo/day/yr was sample submitted		
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Welded	Threaded Clamped
	Blank casing diameter 5 in.	to 30 ft.	Dia. in.	to ft.	Dia. in.	to ft.
	Casing height above land surface: 12 in.,	Weight: 2.35 lbs. / ft.			Wall thickness or gauge No. .214	
	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)			
	SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped 7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)			
	SCREEN - PERFORATION INTERVAL From 30 ft. to 70 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.
	GRAVEL PACK INTERVALS: From 24 ft. to 70 ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.
6	GROUT MATERIALS: 1. Neat cement Grout Intervals: From 4 ft. to 24 ft.,	2. Cement Grout From ft. to ft.,	3. Bentonite ft.,	Other ft.,	bentonite hole plug From ft. to ft.,	
	What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)	
	Direction from well? North	How many feet? 50 feet plus				
	From 0 To 3 topsoil	LITHOLOGIC LOG		From 0 To 3	LITHOLOGIC LOG	
	From 3 To 10 clay			From 3 To 10		
	From 10 To 35 tan shale			From 10 To 35		
	From 35 To 70 limestone/gypsum/gray shale			From 35 To 70		
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3/7/2006 and this record is true to the best of my knowledge and belief.					
	Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 3/10/2006				
	under the business name of Harp Well & Pump Service Inc.	by (signature) <i>Todd S. Harp</i>				