


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 SW 1/4 SW 1/4	SECTION NUMBER 7	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 13th St. N. and Andover Rd., 1/4 mile West, 1/4 mile North Andover, Kansas							
2 WATER WELL OWNER: MURRY	Board of Agriculture, Division of Water Resource						
RR#, ST. ADDRESS, BOX #: 715 W. Point Place	ZIP CODE:	Application Number:					
CITY, STATE: Andover, Kansas							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 101 ft.	ELEVATION: ft.	ft.				
Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL	41 FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr:	3/13/06				
Pump test data: Est. Yield: gpm	Well water was	ft. after	hours of pumping @	gpm			
Bore Hole Diameter 12 in.	Well water was	ft. after	hours of pumping @	gpm			
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only	8. Air conditioning	9. Dewatering	10. Monitoring well	11. Injection well			
2. Irrigation 4. Industrial 6. Oil field water supply	12. Other (Specify below)	; If yes, what mo/day/yr was sample					
Was a chemical/bacteriological sample submitted to Department? YES NO	Was Water Well Disinfected? YES	NO	YES	NO			
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS: Glued	Threaded		
4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded	Clamped		
Blank casing diameter 5 in.	to 41 ft.,	Dia.	in. to	ft., Dia.	in. to ft.		
Casing height above land surface: 24 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC	9. ABS	10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)		
2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)			
SCREEN - PERFORATION INTERVAL	From	41 ft.	to 101 ft.,	From	ft.		
	From	ft.	to	ft.	to		
GRAVEL PACK INTERVALS:	From	24 ft.	to 101 ft.,	From	ft.		
	From	ft.	to	ft.	to		
6 GROUT MATERIALS:	1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug		
Grout Intervals:	From 4 ft.	to 24 ft.,	From ft. to	ft.,	From ft. to ft.		
What is the nearest source of possible contamination:							
1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well		
2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)		
3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage				
Direction from well?: East	How many feet? 50 feet plus						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	topsoil					
3	10	clay					
10	55	tan shale					
55	101	gray shale/ limestone					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and							
was completed on (mo/day/year) 3/13/2006	and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 3/15/2006						
under the business name of Harp Well & Pump Service Inc.	by (signature)					<i>J. d. S. Harp</i>	