


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction 1/4 1/4 NW 1/4	Section Number 7	Township Number T 27S S	Range Number R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 1931 Northridge Andover, Kansas 67002								
2 WATER WELL OWNER:		Granier c/o McCollom Construction 401 State St., Augusta, KS 67010		Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 90 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 4/2/98 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 90 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No						
5 TYPE OF BLANK CASING USED:		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued X Clamped Welded Threaded				
1 Steel 3 RMP (SR) 2 PVC 4 ABS								
Blank casing diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.								
Casing height above land surface 15 in., weight		lbs./ft. Wall thickness or gauge No. SDR26						
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel		5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify)				
12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)				
SCREEN-PERFORATED INTERVALS: From 40 ft. to 90 ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From 20 ft. to 90 ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout		3 Bentonite	4 Other					
Grout Intervals: From 4 ft. to 20 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)				
Direction from well?								
FROM		TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	10	Clay						
10	25	Clay & Shale						
25	40	Lime						
40	60	Shale						
60	75	Shale with Lime Streaks						
75	90	Cherty Lime						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, <input type="checkbox"/> reconstructed or <input type="checkbox"/> plugged under my jurisdiction and was completed on (mo/day/year) 4/2/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 171 This Water Well Record was completed on (mo/day/yr) 4/6/98 under the business name of G & S Drilling, Inc.						by (signature) 		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								