


1 LOCATION OF WATER WELL:		FRACTION			Water Well Record Form WWL-3 KSA 62A-1212			Section Number		Township Number		Range Number		
Butler		NE	1/4	NW	1/4	SW	1/4	19		T 27 S		R 3E E/W		
Distance and direction from nearest town or city street address of well if located within city?														
1416 North Point Court							Andover, Kansas							
WATER WELL OWNER:		ZIEGLER, Mark					Board of Agriculture, Division of Water Resource							
RR#, ST. ADDRESS, BOX #:		1416 North Point Court					Application Number:							
CITY, STATE, ZIP CODE:		Andover, Kansas												
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL			80	ft.	ELEVATION:							
		Depth(s) groundwater Encountered			1	ft.	2	ft.	3	ft.				
		WELL'S STATIC WATER LEVEL 25			FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 02/28/1998									
		Pump test data:			Well water was		ft.	after	hours pumping		gpm			
		Est. Yield gpm:			Well water was		ft.	after	hours pumping		gpm			
		Bore Hole Diameter 12 in.			to 80		ft.	and	in. to		ft.			
		WELL WATER TO BE USED AS:			5 Public water supply		8 Air conditioning		11 Injection well					
		1 Domestic			3 Feedlot	6 Oil field water supply	9 Dewatering		12 Other (Specify below)					
		2 Irrigation			4 Industrial	7 Lawn and garden only	10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes			No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted									
					Water Well Disinfected? Yes <input checked="" type="checkbox"/> No									
5 TYPE OF CASING USED:		5 Wrought iron			8 Concrete tile		CASING JOINTS:		Glued <input checked="" type="checkbox"/> Clamped					
1 Steel		6 Asbestos-Cement			9 Other (Specify below)				Welded					
2 PVC		7 Fiberglass			SDR-26				Threaded					
Blank casing Diameter 5 in. to 40		ft., Dia	in. to	ft., Dia	in. to	ft.								
Casing height above land surface 12 in.,		weight 2.35	lbs. / ft.	7 PVC	Wall thickness or gauge No. 10 Asbestos-cement	.214								
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass			8 RMP (SR)				11 other (specify)					
1 Steel		6 Concrete tile			9 ABS				12 None used (open hole)					
2 Brass														
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped			8 Saw cut				11 None (open hole)					
1 Continous slot		6 Wire wrapped			9 Drilled holes									
2 Louvered shutter		7 Torch cut			10 Other (specify)									
SCREEN-PERFORATION INTERVALS:		from 40	ft. to 80	ft. From										
		from	ft. to	ft. From										
GRAVEL PACK INTERVALS:		from 24	ft. to 80	ft. From										
		from	ft. to	ft. From										
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other	bentonite hole plug								
Grout Intervals: From 4 ft. to 24		ft. From	ft. to	ft. From	ft. to									
What is the nearest source of possible contamination:														
1 Septic tank		4 Lateral lines			7 Pit privy		10 Livestock pens		14 Abandon water well					
2 Sewer lines		5 Cess pool			8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well					
3 Watertight sewer lines		6 Seepage pit			9 Feedyard		12 Fertilizer storage		16 Other (specify below)					
Direction from well? West		How many feet? 15												
FROM		TO	LITHOLOGIC LOG			FROM	TO	PLUGGING INTERVALS						
0	4	topsoil												
4	16	clay												
16	80	shale												
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/28/1998 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 03/03/98. Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Todd S. Harp</i>														