


1 LOCATION OF WATER WELL: Butler		FRACTION NE 1/4 SW 1/4 SW 1/4			Section Number 19	Township Number T 27 S	Range Number R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 1219 Red Bud Andover, Kansas							
WATER WELL OWNER: SCHROEDER, Bill		Board of Agriculture, Division of Water Resource					
RR#, ST. ADDRESS, BOX #: 1219 Red Bud		Application Number:					
CITY, STATE, ZIP CODE: Andover, Kansas							
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 85 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft. WELL'S STATIC WATER LEVEL 21 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 04/14/1998 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 85 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes submitted		No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was Water Well Disinfected? Yes <input checked="" type="checkbox"/> No					
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile Casing JOINTS: Glued <input checked="" type="checkbox"/> Clamped 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass SDR-26 Threaded					
Blank casing Diameter 5 in. to 25 ft., Dia in. to ft., weight 2.35 lbs. / ft.		Wall thickness or gauge No. .214 10 Asbestos-cement					
Casing height above land surface 12 in.,		7 PVC					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVALS: from 25 ft. to 85 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: from 24 ft. to 85 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.		10 Livestock pens 14 Abandon water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below)					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard West							
Direction from well? 20 How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	3	topsoil					
3	41	brown shale					
41	85	grey shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/14/1998 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 04/16/98 . Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Todd S. Harp</i>							