


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 NW 1/4 SW 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W	
Distance and direction from nearest town or city street address of well if located within city?						
708 Crescent Lakes Andover, Kansas						
2	WATER WELL OWNER: H & H HOMEBUILDERS	Board of Agriculture, Division of Water Resource				
RR#, ST. ADDRESS, BOX #: 3865 N. Lakecrest Ct.		Application Number:				
CITY, STATE: Wichita, Kansas		ZIP CODE:				
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  1 Mile	4 DEPTH OF COMPLETED WELL: 80 ft.	ELEVATION:			
Depth of groundwater Encountered: ft. ft. ft.						
WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/6/06						
Pump test data: Well water was ft. after hours of pumping @ gpm						
Est. Yield: gpm Well water was ft. after hours of pumping @ gpm						
Bore Hole Diameter 12 in. to 80 ft. and in. to ft.						
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES NO 12. Other (Specify below) Was Water Well Disinfected? YES NO						
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below)			CASING JOINTS: Glued Threaded		
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded					Clamped	
Blank casing diameter 5 in. to 40 ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)						
SCREEN - PERFORATION INTERVAL From 40 ft. to 80 ft., From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 24 ft. to 80 ft., From ft. to ft., From ft. to ft.						
6	GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug					
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage						
Direction from well? South How many feet? 50 ft. plus						
From To LITHOLOGIC LOG			From To	LITHOLOGIC LOG		
0	4	topsoil				
4	10	clay				
10	70	shale				
70	80	limestone				
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and					
was completed on (mo/day/year) 7/06/2006			and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236			This water well record was completed on (mo/day/year) 7/10/2006			
under the business name of Harp Well and Pump Service			by (signature) 