


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SE 1/4 SW 1/4 NW 1/4	SECTION NUMBER 7	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city: 1809 Buckthorn Ct. Andover, Kansas							
2 WATER WELL OWNER: LEBBIN, Mark	RR#, ST. ADDRESS, BOX #: 1809 Buckthorn Ct.	Board of Agriculture, Division of Water Resource					
CITY, STATE: Andover, Kansas		ZIP CODE:	Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 115 ft.	ELEVATION:					
	Depth of groundwater Encountered:	ft.	ft.	ft.			
	WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr:	7/12/06				
	Pump test data: Est. Yield: gpm	Well water was	ft. after	hours of pumping @ gpm			
	Bore Hole Diameter 12 in.	Well water was	ft. after	hours of pumping @ gpm			
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply Was a chemical/bacteriological sample submitted to Department?	7. Lawn and garden only	9. Dewatering	11. Injection well			
	8. Air conditioning	10. Monitoring well	12. Other (Specify below)				
	YES	NO	; if yes, what mo/day/yr was sample submitted				
	Was Water Well Disinfected? YES NO						
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS: Glued			
	6. Asbestos-Cement	8. Concrete tile	SDR-26	Threaded Welded Clamped			
Blank casing diameter 5 in.	to 30 ft.	Dia.	in. to	ft. Dia. in. to ft.			
Casing height above land surface: 12 in.,		Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC	9. ABS	11. Other (specify)				
	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes	11. None (open hole) 10. Other (specify)				
SCREEN - PERFORATION INTERVAL	From 30 ft. to 115 ft.,		From	ft.	to ft.		
	From ft. to ft.,		From	ft.	to ft.		
GRAVEL PACK INTERVALS:	From 24 ft. to 115 ft.,		From	ft.	to ft.		
	From ft. to ft.,		From	ft.	to ft.		
6 GROUT MATERIALS: 1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug			
Grout Intervals: From 4 ft. to 24 ft.,	From ft. to	ft.,	From	ft. to	ft.		
What is the nearest source of possible contamination:							
1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)			
Direction from well? North How many feet? 50 ft. plus							
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	topsoil					
3	12	clay					
12	115	grey shale					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 7/12/2006 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236				This water well record was completed on (mo/day/year) 7/14/2006			
under the business name of Harp Well and Pump Service				by (signature) <i>Todd S. Harp</i>			