


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 NW 1/4 SE 1/4	SECTION NUMBER 19	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 118 S. Putter Road Andover, Kansas							
2 WATER WELL OWNER: GRIMSLEY, Dawson	RR# ST. ADDRESS, BOX #: 118 S. Putter Road	Board of Agriculture, Division of Water Resource					
CITY, STATE: Andover, Kansas	ZIP CODE:	Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 95 ft.	ELEVATION:					
1 Mile	Depth of groundwater Encountered:	ft.	ft.				
WELL'S STATIC WATER LEVEL Pump test data: Est. Yield: gpm Bore Hole Diameter 12 in.	35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Well water was ft. after hours of pumping @ gpm Well water was ft. after hours of pumping @ gpm to 95 ft. and in. to ft.	10/24/06					
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? Was Water Well Disinfected?	9. Dewatering 11. Injection well 10. Monitoring well ; If yes, what mo/day/yr was sample submitted YES NO YES NO	12. Other (Specify below)					
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped							
Blank casing diameter 5 in. to 45 ft., Dia. in. to ft., Dia. in. to ft.							
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)							
SCREEN - PERFORATION INTERVAL	From 45 ft.	to 95 ft.,	From	ft. to ft.			
	From ft.	to ft.,	From	ft. to ft.			
GRAVEL PACK INTERVALS:	From 24 ft.	to 95 ft.,	From	ft. to ft.			
	From ft.	to ft.,	From	ft. to ft.			
6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 2. Cement Grout 3. Bentonite	Other	bentonite hole plug				
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage							
Direction from well? North	How many feet? 25						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	4	topsoil					
4	30	clay					
30	80	shale					
80	95	limestone and shale					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10-24-2006 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 10-25-2006						
under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp						