


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 SE 1/4 SE 1/4	SECTION NUMBER 6	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city?							
2413 Fieldstone		(1/4 mile N. of 21st St. North and 1/8th mile West of Andover Rd.)		Andover, Kansas			
2 WATER WELL OWNER: KLAUSMEYER CONSTRUCTION	RR#, ST. ADDRESS, BOX #: 10008 W. York	Board of Agriculture, Division of Water Resource					
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 100 ft.	ELEVATION: ft. ft. ft.					
Depth of groundwater Encountered:							
WELL'S STATIC WATER LEVEL Pump test data: Est. Yield: gpm	40 FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr:	11/17/06				
Bore Hole Diameter 12 in.	to 100 ft.	ft. and in.	ft. to ft.	ft.			
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 2. Irrigation 4. Industrial 6. Oil field water supply Was a chemical/bacteriological sample submitted to Department? submitted	7. Lawn and garden only	9. Dewatering	11. Injection well				
	8. Air conditioning	10. Monitoring well	12. Other (Specify below)				
Was Water Well Disinfected?	YES	NO	; If yes, what mo/day/yr was sample				
	YES	NO					
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS: Glued			
4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded			
Blank casing diameter 5 in. to 30 ft.,	Dia. in.	to ft.	Dia. in.	to ft.			
Casing height above land surface: 24 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC	9. ABS	11. Other (specify)				
8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes	11. None (open hole) 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 30 ft. to 100 ft.,	From 30 ft. to 100 ft.,	From 30 ft. to 100 ft.,	From 30 ft. to 100 ft.,	From 30 ft. to 100 ft.,			
GRAVEL PACK INTERVALS: From 24 ft. to 100 ft.,	From 24 ft. to 100 ft.,	From 24 ft. to 100 ft.,	From 24 ft. to 100 ft.,	From 24 ft. to 100 ft.,			
6 GROUT MATERIALS: 1. Neat cement Grout Intervals: From 4 ft. to 24 ft.,	2. Cement Grout From 4 ft. to 24 ft.,	3. Bentonite ft. to ft.,	Other	bentonite hole plug			
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)			
Direction from well?: East	How many feet? 40 ft. plus						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	topsoil					
3	10	clay					
10	45	tan shale					
45	100	gray and black shale with limestone					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 11-17-2006 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 11-20-2006						
under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp						