

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL:	FRACTION	NE 1/4	SE 1/4	SW 1/4	SECTION NUMBER	6	TOWNSHIP NUMBER	T 27 S	RANGE NUMBER	R 3E E/W
Distance and direction from nearest town or city street address of well if located within city?											
2407 N. Fieldstone Andover, Kansas											
2	WATER WELL OWNER:	KLAESMEYER CONSTRUCTION					Board of Agriculture, Division of Water Resource				
RR#, ST. ADDRESS, BOX #:			10008 W. York			ZIP CODE:			Application Number:		
CITY, STATE:			Wichita, Kansas								
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	N		E		W		S		1 Mile	
		NW		NE		SW		SE			
4 DEPTH OF COMPLETED WELL: 98 ft. ELEVATION:											
Depth of groundwater Encountered: ft. ft.											
WELL'S STATIC WATER LEVEL 26 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 11/13/06											
Pump test data: Well water was ft. after hours of pumping @ gpm											
Est. Yield: gpm Well water was ft. after hours of pumping @ gpm											
Bore Hole Diameter 12 in. to 98 ft. and in. to ft.											
WELL WATER TO BE USED AS:											
1. Domestic 3. Feedlot 5. Public water supply 7. <u>Lawn and garden only</u> 9. Dewatering 11. <u>Injection well</u>											
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well											
12. Other (Specify below)											
Was a chemical/bacteriological sample submitted to Department? YES <u>NO</u> ; If yes, what, mo/day/yr was sample submitted											
Was Water Well Disinfected? <u>YES</u> NO											
5	TYPE OF CASING USED:	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS:		Glued	Threaded	
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped											
Blank casing diameter 5 in. to 28 ft., Dia. in. to ft., Dia. in. to ft.											
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)											
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)											
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)											
SCREEN - PERFORATION INTERVAL From 28 ft. to 98 ft., From ft. to ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From 24 ft. to 98 ft., From ft. to ft., From ft. to ft.											
6	GROUT MATERIALS:	1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug					
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well											
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)											
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage											
Direction from well? East How many feet? 50 ft. plus											
From To LITHOLOGIC LOG From To LITHOLOGIC LOG											
0	3	topsoil									
3	10	clay									
10	65	tan shale									
65	97	gray shale									
97	98	limestone									
7	Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. <u>reconstructed</u> or 3. <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 11-13-2006 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 236					This water well record was completed on (mo/day/year) 11/15/2006						
under the business name of Harp Well and Pump Service					by (signature) Todd S. Harp						