


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	FRACTION SW 1/4 NW 1/4 NE 1/4	SECTION NUMBER 19	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city?							
915 W. 2nd Andover, Kansas							
2 WATER WELL OWNER:	JACKSON, Joey		Board of Agriculture, Division of Water Resource				
RR#, ST. ADDRESS, BOX #:	915 W. 2nd						
CITY, STATE:	Andover, Kansas		ZIP CODE:	Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 90 ft. ELEVATION:  Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 11/20/06 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 90 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES 12. Other (Specify below) Was Water Well Disinfected? YES ; If yes, what mo/day/yr was sample submitted NO						
5 TYPE OF CASING USED:	1. Steel 2. PVC	3. RPM (SR) 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile SDR-26	CASING JOINTS: Glued Welded Clamped		
Blank casing diameter	5 in.	to 50 ft.	Dia.	in. to ft.	Dia. in. to ft.		
Casing height above land surface:	12 in.		Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214			
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 2. Brass	3. Stainless Steel 4. Galvanized	5. Fiberglass 6. Concrete Tile	7. PVC 8. RMP (SR)	9. ABS 10. Asbestos-Cement	11. Other (specify) 12. None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 2. Louvered shutter	3. Mill slot 4. Key punched	5. Gauzed wrapped 6. Wire wrapped	7. Torch cut 8. Saw cut	9. Drilled holes 10. Other (specify)	11. None (open hole)		
SCREEN - PERFORATION INTERVAL		From 50 ft.	to 90 ft.,	From ft.	to ft.		
GRAVEL PACK INTERVALS:		From ft.	to ft.	From ft.	to ft.		
From ft.		to ft.	From ft.	to ft.			
6 GROUT MATERIALS:	1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug		
Grout Intervals:	From 4 ft.	to 24 ft.	From ft.	to ft.,	From ft. to ft.		
What is the nearest source of possible contamination:							
1. Septic tank 2. Sewer lines 3. Watertight sewer line	4. Lateral lines 5. Cess Pool	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)		
Direction from well?	North				How many feet? 50 ft. plus		
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	4	topsoil					
4	15	clay					
15	90	shale					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 11-20-2006 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236			This water well record was completed on (mo/day/year) 11-22-2006				
under the business name of Harp Well and Pump Service			by (signature) <i>Todd S. Harp</i>				