


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SW 1/4 NW 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 832 Crescent Lakes Andover, Kansas				
2 WATER WELL OWNER: H & H Home Builders Inc.	RR#, ST. ADDRESS, BOX #: 3865 N. Lakecrest Ct.	Board of Agriculture, Division of Water Resource		
CITY, STATE: Wichita, Kansas		ZIP CODE:	Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 97 ft.	ELEVATION:		
Depth of groundwater Encountered:				ft.
WELL'S STATIC WATER LEVEL	35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr:	1/10/07		
Pump test data: Est. Yield: gpm	Well water was	ft. after	hours of pumping @	gpm
Bore Hole Diameter 12 in.	Well water was	ft. after	hours of pumping @	gpm
WELL WATER TO BE USED AS:	9. Dewatering 11. Injection well			
1. Domestic 3. Feedlot 5. Public water supply	7. Lawn and garden only	12. Other (Specify below)		
2. Irrigation 4. Industrial 6. Oil field water supply	8. Air conditioning	10. Monitoring well		
Was a chemical/bacteriological sample submitted to Department? submitted		YES	NO	; If yes, what mo/day/yr was sample
		Was Water Well Disinfected?	YES	NO
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	9. Other (Specify below)	CASING JOINTS:		Glued Welded Threaded
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile	SDR-26			Clamped
Blank casing diameter 5 in. to 37 ft., Dia.	in.	to	ft.	in. to ft.
Casing height above land surface: 12 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. Steel 3. Stainless Steel 5. Fiberglass	7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)	
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)		
SCREEN - PERFORATION INTERVAL	From 37 ft. to 97 ft.,	From	ft.	to ft.
	From ft. to ft.,	From	ft.	to ft.
GRAVEL PACK INTERVALS:	From 24 ft. to 97 ft.,	From	ft.	to ft.
	From ft. to ft.,	From	ft.	to ft.
6 GROUT MATERIALS:	1. Neat cement 2. Cement Grout 3. Bentonite	Other	bentonite hole plug	
Grout Intervals: From 4 ft. to 24 ft.,	From ft. to ft.,	From	ft.	to ft.
What is the nearest source of possible contamination:				
1. Septic tank 4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)
3. Watertight sewer line 6. Seepage pit	9. Feed yard	12. Fertilizer storage		
Direction from well? East	How many feet? 50 ft. plus			
From	To	LITHOLOGIC LOG		
0	4	topsoil		
4	15	clay and fine sand		
15	85	shale		
85	97	limestone		
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and				
was completed on (mo/day/year) 1-10-2007		and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 236		This water well record was completed on (mo/day/year) 1-15-2007		
under the business name of Harp Well and Pump Service		by (signature) Todd S. Harp		