


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		FRACTION SE 1/4 NE 1/4 SE 1/4			SECTION NUMBER 6		TOWNSHIP NUMBER T 27 S			R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city?													
Andover Cornerstone Addition (#3 Fieldstone & Cornerstone Parkway) Andover, Kansas													
2 WATER WELL OWNER:		RITCHIE DEVELOPMENT			Board of Agriculture, Division of Water Resource								
RR#, ST. ADDRESS, BOX #:		8100 E. 22nd St. N. #1000			Application Number:								
CITY, STATE:		Wichita, Kansas+			ZIP CODE: 67226								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 127 ft.			ELEVATION:								
		Depth of groundwater Encountered: ft. ft. ft.											
		WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 2/5/07											
		Pump test data: Well water was ft. after hours of pumping @ gpm											
		Est. Yield: gpm Well water was ft. after hours of pumping @ gpm											
		Bore Hole Diameter 12 in. to 127 ft. and in. to ft.											
		WELL WATER TO BE USED AS:			9. Dewatering 11. Injection well								
		1. Domestic 3. Feedlot 5. Public water supply 7. <u>Lawn and garden only</u>			12. Other (Specify below)								
		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning			10. Monitoring well								
		Was a chemical/bacteriological sample submitted to Department? YES <u>NO</u>			; If yes, what mo/day/yr was sample submitted								
		Was Water Well Disinfected? <u>YES</u> <u>NO</u>											
5 TYPE OF CASING USED:		5. Wrought Iron 7. Fiberglass 9. Other (Specify below)			CASING JOINTS: <u>Glued</u>		Threaded						
1. Steel 3. RPM (SR) 2. PVC 4. ABS		6. Asbestos-Cement 8. Concrete tile			Welded		Clamped						
Blank casing diameter 5 in. to 47 ft.		Dia.											
Casing height above land surface: 12 in.		Weight: 2.35 lbs. / ft.			Wall thickness or gauge No. .214								
TYPE OF SCREEN OR PERFORATION MATERIAL:													
1. Steel 3. Stainless Steel 2. Brass 4. Galvanized		5. Fiberglass 7. <u>PVC</u> 6. Concrete Tile 8. RMP (SR)			9. ABS 10. Asbestos-Cement		11. Other (specify) 12. None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:													
1. Continuous slot 3. Mill slot 2. Louvered shutter 4. Key punched		5. Gauzed wrapped 6. Wire wrapped			7. Torch cut 8. <u>Saw cut</u>		9. Drilled holes 10. Other (specify)		11. None (open hole)				
SCREEN - PERFORATION INTERVAL From 47 ft.		to 127 ft.			From ft.		to ft.		to ft.				
GRAVEL PACK INTERVALS: From 24 ft.		to 127 ft.			From ft.		to ft.		to ft.				
From ft.		to ft.			From ft.		to ft.		to ft.				
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite		4. Lateral lines 5. Cess Pool 6. Seepage pit			7. Pit privy 8. Sewage lagoon 9. Feed yard		10. Livestock pens 11. Fuel storage 12. Fertilizer storage		Other		bentonite hole plug		
Grout Intervals: From 4 ft.		to 24 ft.			From ft.		to ft.		From ft.		to ft.		
What is the nearest source of possible contamination:													
1. Septic tank 2. Sewer lines 3. Watertight sewer line		4. Lateral lines 5. Cess Pool 6. Seepage pit			7. Pit privy 8. Sewage lagoon 9. Feed yard		10. Livestock pens 11. Fuel storage 12. Fertilizer storage		13. Insecticide storage 14. Abandon water well		15. Oil well/Gas well 16. Other (specify below)		
Direction from well? West How many feet? 50 ft. plus													
From		To		LITHOLOGIC LOG			From		To		LITHOLOGIC LOG		
0	4	topsoil											
4	18	clay											
18	127	shale											
<p>7 Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. <u>reconstructed</u> or 3. <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 2-5-2007 and this record is true to the best of my knowledge and belief.</p>													
Kansas Water Well Contractor's License No. 236						This water well record was completed on (mo/day/year) 2-12-2007							
under the business name of Harp Well and Pump Service						by (signature) Todd S. Harp							