


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1	LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 SE 1/4 SE 1/4	SECTION NUMBER 31	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 415 Pepperridge Andover, Kansas					
2	WATER WELL OWNER: MC CLURE, Monica	Board of Agriculture, Division of Water Resource 415 Pepperridge Andover, Kansas			
RR#, ST. ADDRESS, BOX #: 415 Pepperridge Andover, Kansas		ZIP CODE: 	Application Number: 		
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 97 ft.	ELEVATION: ft.		
Depth of groundwater Encountered: ft. ft.					
WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 1/24/07					
Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm					
Bore Hole Diameter 12 in. to 97 ft. and in. to ft.					
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? YES NO 9. Dewatering 11. Injection well Was Water Well Disinfected? YES NO 10. Monitoring well 12. Other (Specify below)					
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile			9. Other (Specify below) SDR-26	CASING JOINTS: Glued Threaded Welded Clamped
Blank casing diameter 5 in. to 37 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)					
SCREEN - PERFORATION INTERVAL From 37 ft. to 97 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft., From ft. to ft.					
6	GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug				
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? South How many feet? 30 ft. plus					
LITHOLOGIC LOG			LITHOLOGIC LOG		
From	To		From	To	
0	4	topsoil			
4	15	clay			
15	97	shale			
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 1-24-2007 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236			This water well record was completed on (mo/day/year) 1-26-2007		
under the business name of Harp Well and Pump Service			by (signature) Todd S. Harp		