

1 LOCATION OF WATER WELL:	Fraction County: Butler	Section Number NW 1/4 SW 1/4 NW 1/4	Township Number T 27 S	Range Number R 3 EW										
Distance and direction from nearest town or city street address of well if located within city? 1533 W Honey South Ct														
2 WATER WELL OWNER:	David Hogan 1533 W Honey South Ct Endover KS				Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITHIN SECTION BOX:	DEPTH OF COMPLETED WELL 73 ft. ELEVATION: <table border="1" style="display: inline-table; vertical-align: middle;"> <tr><td colspan="2">N</td></tr> <tr><td>W</td><td>E</td></tr> <tr><td>W</td><td>E</td></tr> <tr><td>SW</td><td>SE</td></tr> <tr><td>S</td><td>N</td></tr> </table> Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 18' ft. below land surface measured on mo/day/yr 10-8-07 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well				N		W	E	W	E	SW	SE	S	N
N														
W	E													
W	E													
SW	SE													
S	N													
4	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No													
5 TYPE OF BLANK CASING USED:	1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued X Clamped Welded Threaded									
Blank casing diameter	5	in. to	673	ft., Dia	in. to ft., Dia in. to ft.									
Casing height above land surface	10	in., weight	100	lbs./ft.	Wall thickness or guage No. 26									
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel 2 Brass	3 Stainless Steel 4 Galvanized Steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Glazed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)									
SCREEN-PERFORATED INTERVALS:	From 50	ft. to 73	ft., From ft. to ft.											
GRAVEL PACK INTERVALS:	From 24	ft. to 73	ft., From ft. to ft.											
6 GROUT MATERIAL:	1 Neat cement Grout Intervals: From 4	2 Cement grout ft. to 24	3 Bentonite ft. to ft., From ft. to ft.	4 Other 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage										
What is the nearest source of possible contamination:	1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)										
Direction from well?	East				How many feet? 36									
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS								
0	2	Top Soil												
2	10	Clay												
10	24	Green Shale												
24	55	Blue Shale												
55	73	Limestone												
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-8-07					and this record is true to the best of my knowledge and belief, Kansas								
Water Well Contractor's Licence No.	611					This Water Well Record was completed on (mo/day/yr) 6-12-07								
under the business name of	Chase Drilling					by (signature) D. Chase								